

East Plant Area TSCA Vault (Revision 1) Annual Report Calendar Year 2023

GM Bedford Casting Operations 105 GM Drive Bedford, Indiana EPA ID# IND0060036099

General Motors, LLC April 30, 2025

Contents

1.	Intro	duction	1
	1.1	Purpose and Organization of Report	1
2.	Sumr	mary of Record Keeping Log	2
	2.1	Summary of LCS, LDS, and GUS Sump Monitoring Logs	2
	2.2	Summary of Water Treated in the Groundwater Treatment Plant	3
	2.3	Summary of the Vault Inspection Log and Maintenance Activities	3
3.	Analy	tical Results	3
	3.1	Groundwater Monitoring Analytical Results	3
	3.2	Leachate and Leak Detection Water Monitoring Analytical Results	4
	3.3	GUS Analytical Results	4
	3.4	Water Treatment Facility Analytical Results	4
4.	Leach	hate and Leak Detection Water Disposal	4
5.	Sumr	nary and Review of Water Elevations	5
	5.1	Leachate Collection System	5
	5.2	Leak Detection System	5
	5.3	Gravel Underdrain System	7
6.	Issue	s Encountered and Remedial Actions	7
7.	Spill	Cleanup Reports	7
8.	Finan	ncial Assurance	7
9.	Refer	rences	8

Table index

2023 Summary of Leachate Collection System Log
2023 Summary of Leak Detection System Log
2023 Summary of Gravel Underdrain System Log
Summary of 2023 Water Elevations Compared to Liner System
2023 LCS, LDS, and GUS Maximum Water Elevation Summary
2023 Summary of Monthly Total Volume of Water Treated
Summary of Analytical Results - El CA750 First Half 2023 Sampling Event
Summary of Analytical Results - El CA750 Second Half 2023 Sampling Event
2023 LCS and LDS Analytical Results
2023 Groundwater Treatment Plant Monitoring Analytical Results

Figure index

Figure 3.1	Groundwater Sampling Locations
Figure 3.2	El CA750 Groundwater Analytical Results for PCBs for First Semi-Annual Event of 2023
Figure 3.3	El CA750 Groundwater Analytical Results for PCBs for Second Semi-Annual Event of 2023
Figure 5.1	Summary of Average Monthly Volume of Water Removed from LCS and LDS

Appendices

Appendix A Cover System Inspection Forms

Terms and Acronyms

ALR action leakage rate
AMSL above mean sea level

AOC Administrative Order on Consent

Approvals U.S. EPA and IDEM PCB Risk-Based Disposal Approvals

BCO Bedford Casting Operations

CA Corrective Action

CFR Code of Federal Regulations
CMP Corrective Measures Proposal
CRA Conestoga-Rovers & Associates

El Environmental Indicator

EQ tank equalization tank

Facility GM Bedford Casting Operations Facility in Bedford, Indiana

ft. foot/feet

GM General Motors LLC gpad gallons/acre/day

GUS gravel underdrain system
GWTP Groundwater Treatment Plant

HASP Health and Safety Plan

IDEM Indiana Department of Environmental Management

IM Interim Measure

LCS leachate collection system
LDS leak detection system
mag meter magnetic flow meter
mg/L milligram per liter

NPDES National Pollutant Discharge Elimination System

PCB Polychlorinated biphenyl
PCP Post-Closure Plan
ppm parts per million

RCRA Resource Conservation and Recovery Act

Report East Plant Area Vault Annual Monitoring Report Covering the

Calendar Year of 2023

SCADA supervisory control and data acquisition

SSC Site Source Control

TSCA Toxic Substance Control Act

ug/L micrograms per liter

U.S. EPA United States Environmental Protection Agency

Vault East Plant Area TSCA landfill vault

1. Introduction

This Annual Monitoring Report (Report) summarizes data from the calendar year 2023 for post-closure monitoring activities for the Toxic Substances Control Act (TSCA) landfill vault (Vault), located in the East Plant Area of the General Motors LLC (GM) Bedford Casting Operations (BCO) Facility (Facility), in Lawrence County, Bedford, Indiana. This Report has been prepared by GHD on behalf of GM in accordance with the Resource Conservation and Recovery Act (RCRA) Administrative Order on Consent effective August 14, 2014 (United States Environmental Protection Agency [U.S. EPA] Docket No. RCRA-05-2014-0011), and the East Plant Area Vault Post-Closure Plan (PCP) (Conestoga-Rovers & Associates [CRA], February 3, 2012; as amended by Revision 1, August 25, 2016). The Vault was constructed as part of the RCRA Corrective Action (CA) activities at the Facility. U.S. EPA and Indiana Department of Environmental Management (IDEM) agency approvals (Approvals) for the Vault were effective October 18, 2006, and were issued pursuant to 40 Code of Federal Regulations (CFR) § 761.61 (c) for the risk-based disposal of polychlorinated biphenyl (PCB) contaminated waste in the Vault. The Vault was constructed as a component of the East Plant Area Interim Measure (IM) during RCRA CA activities initiated under the Performance Based CA Agreement (effective March 20, 2001, and amended October 1, 2002, March 29, 2007, and May 9, 2008). A RCRA administrative order between U.S. EPA and GM was executed on August 4, 2014 (Administrative Order on Consent (AOC) EPA Docket No. RCRA-05-2014-0011) and replaces the Performance-Based CA Agreement, which has been terminated.

Final closure of the Vault occurred on March 27, 2012. The PCP was submitted to U.S. EPA on February 3, 2012 and amended on August 25, 2016, outlining the post-closure monitoring of the Vault which includes documentation of the quantity of liquid collected from the leachate collection system (LCS), leak detection system (LDS), and gravel underdrain system (GUS); the water elevations in these systems; analytical results from samples collected from these systems; and effluent quantity/quality from the on-site groundwater treatment plant (GWTP). The PCP prescribes a reduced frequency of record keeping procedures to occur, at a minimum, once per month. Additional post-closure monitoring required by the PCP includes annual inspections of the Vault cover system. Consistent with the PCP and the RCRA AOC, the next annual report covering post-closure monitoring data for the 2024 calendar year will be submitted to U.S. EPA on or before July 15, 2025.

Daily operation and maintenance activities associated with the GWTP, LCS, LDS, GUS, and wet wells are conducted by Treatment Technologies under the direction of GM.

1.1 Purpose and Organization of Report

This Report summarizes the 2023 Vault monitoring requirements set out in the PCP and the Approvals by U.S. EPA and IDEM. This Report is organized as follows:

Section 2.0 - Summary of Record Keeping Log

This section provides a summary of the quantity of liquid collected in 2023 from the LCS and LDS sumps and discharged from these systems to the GWTP for treatment; along with water elevations in the GUS, over the primary liner (LCS), and over the secondary liner (LDS).

Section 3.0 - Analytical Results

This section provides analytical results for 2023 from the monitoring of the LCS, LDS, and combined effluent from the GWTP, and groundwater monitoring wells near the Vault.

Section 4.0 - Leachate and Leak Detection Water Disposal

This section provides details related to the volume, PCB concentration, and disposal for leachate and leak detection water with a PCB concentration equal to or greater than (≥) 1 part per million (ppm), if any.

Section 5.0 - Summary and Review of Water Elevations

This section provides a summary and review of the water elevations and depth over the primary liner (LCS), the secondary liner (LDS), and in the GUS.

Section 6.0 - Issues Encountered and Rectification Actions

This section identifies issues and/or problems encountered related to the Vault (i.e., performance of monitoring systems, analytical results, physical characteristics, etc.) and actions taken to rectify them.

Section 7.0 - Spill Cleanup Reports

This section identifies any PCB spill cleanups as established in accordance with the site Health and Safety Plan (HASP).

Section 8.0 - Financial Assurance

This section discusses financial assurance for the Vault.

Section 9.0 - References

This section presents references cited in this Report.

2. Summary of Record Keeping Log

The following information was recorded, as required by the PCP:

- 1. The quantity of liquid collected from the LCS.
- 2. The quantity of liquid collected from the LDS.
- 3. The quantity of liquid collected from the GUS.
- The elevation of liquid over the primary liner, the secondary liner, and in the GUS
- 5. The amount of water (liquid) discharged from the LCS, LDS, and GUS to the GWTP, and the respective PCB concentration.
- 6. The Vault inspection logs and maintenance activities.

2.1 Summary of LCS, LDS, and GUS Sump Monitoring Logs

In 2023, automated daily water level readings, measured by transducers, were collected from the GUS and LCS sumps. Data was recorded and stored in the GWTP though the supervisory control and data acquisition (SCADA) system. Water levels in the LDS and LCS systems were manually measured using a water level tape and recorded on a weekly basis. Summaries of the sump monitoring logs for the LCS, LDS, and GUS including the quantity of liquid pumped from each of the Vault collection systems are presented in Tables 2.1, 2.2, and 2.3, respectively. In 2023, field data for the LCS, LDS, and GUS were directly entered into an electronic form (see Tables 2.1, 2.2, and 2.3). Water pumped from the LCS and LDS is treated and managed in compliance with the National Pollutant Discharge Elimination System (NPDES) permit (NPDES Permit No. IN0064424) for the site.

Table 2.4 presents a summary of the water elevations to allow for direct comparison between the various layers of the Vault liner system (listed in order from top to bottom: LCS, lowest point of the primary liner system, LDS, lowest point of the secondary liner system, and GUS). Table 2.5 presents a summary of the monthly maximum water elevation in each of the sumps.

2.2 Summary of Water Treated in the Groundwater Treatment Plant

Water removed from the Vault sumps is directed to the GWTP, which treats PCB impacted water removed from the Vault Sumps and the Site Source Control (SSC) wet wells (including wet wells #1 through #5). Approximately 35,801 gallons of water were removed from the LCS and 425.7 gallons from the LDS during 2023. There was no water removed from the GUS during the reporting period. The GWTP discharge at Outfall 004 is sampled monthly under NPDES Permit No. IN0064424. Data collected during the 2023 calendar year were reported in accordance with the NPDES permit.

The volume of water discharged from the GWTP is recorded daily. A summary of the total monthly volume and daily average of treated water in the GWTP for 2023 is provided in Table 2.6.

2.3 Summary of the Vault Inspection Log and Maintenance Activities

Maintenance and inspection activities were performed at the Vault during the 2023 calendar year.

GHD completed inspection of the Vault Cover System on a semi-annual basis, concurrent with inspection of the West Plant Area and East Plant Area Cover Systems. These inspections were completed on May 23, 2023, and November 20, 2023. The findings of these inspections were previously reported in the semi-annual progress reports (GM 2023, GM 2024). The inspection forms are provided in Appendix A. There were no significant findings posing a risk to the integrity of the Vault cover system.

The volume of water extracted from the LCS is recorded by a magnetic flow meter (mag meter) located along the forcemain at the LCS sump that records only the volume pump from the LCS. The volume of war extracted from the LDS is manually recorded by a separate in-line paddlewheel flow meter. The mag meter calibration is conducted biennially. The calibration of the mag meter was last conducted on August 29, 2022. The next calibration will be conducted in the 2024 calendar year. There are no calibration requirements for the paddlewheel flow meter. However, the operator routinely inspects the paddlewheel for debris, wear and tear. Batteries are replaced when necessary.

3. Analytical Results

Sampling methods and analytical procedures were performed in compliance with 40 CFR Part 136, as amended in 41 FR 52779 on December 1, 1976.

3.1 Groundwater Monitoring Analytical Results

Groundwater sampling specific to the Vault is conducted at locations 9-4 and CH-20. Sampling at these locations is coordinated with the semi-annual Environmental Indicator (EI) CA750 monitoring program. Groundwater monitoring (static water levels and/or sampling) locations under the EI CA750 in the vicinity of the Vault are shown on Figure 3.1.

Static groundwater levels, measured quarterly, are consistent with historical elevations. There is no evidence of a release from the Vault to the groundwater table based on unusual changes in water elevations in the LCS, LDS, and GUS sumps (Table 2.4) or based on static groundwater levels in the vicinity of the Vault.

Locations 9-4 and CH-20 are downgradient of the Vault. Groundwater results for 9-4 showed PCB concentrations of 0.33 ug/L (May 2023) and 0.34 ug/L (December 2023). PCBs were not detected in CH-20 groundwater in either event.

The 2023 groundwater sampling events were conducted May 22 -25 and November 13-16. Results were previously reported in the EI CA750 sampling summary memoranda (GHD 2023, GHD 2024) and are summarized in Table 3.1

and Figure 3.2 for the May event and Table 3.2 and Figure 3.3 for the November event. These results are consistent with historical results.

3.2 Leachate and Leak Detection Water Monitoring Analytical Results

The PCP requires water from the LCS and LDS to be sampled at least monthly for PCBs, contingent on the presence of sufficient water to collect a sample. Treatment Technologies collected samples from both the LCS and LDS monthly.

During the calendar year 2023, monthly samples were collected form the LCS. Samples were analyzed for PCBs and VOCs. PCB concentrations ranged from 0.16 to 0.83 ug/L. VOC concentrations were below detection limits. Monthly sample collection was attempted from the LDS. Samples were not collected in April and December due to insufficient volume. PCB concentrations ranged from non-detect to 0.16 ug/L. Results for samples collected at the LCS and LDS are consistent with past results following completion on the Vault cover liner installation. Analytical results are presented in Table 3.3.

3.3 GUS Analytical Results

There was no sampling completed at the GUS in 2023. The GUS sump is no longer available as a sampling or extraction point due to obstructions and inoperable pumps within the sump.

3.4 Water Treatment Facility Analytical Results

Water removed from the LCS and LDS are directed via permanent forcemain to the GWTP's equalization tank. The Vault water is combined with groundwater from the Site Source Control (SSC) Wet Wells #1 through #3 and the two trench collection systems, Wet Wells #4 and #5, prior to treatment and discharge under NPDES Permit No. IN0064424.

The GWTP was sampled monthly in accordance with the NPDES permit. Effluent results for total PCBs were non detect during the reporting year. Analytical results for 2023 monthly Outfall 004 discharge sampling events are presented in Table 3.4.

4. Leachate and Leak Detection Water Disposal

Pursuant to U.S. EPA's Risk Based Approval to Dispose of PCBs dated October 18, 2006; Conditions of Approval; Leachate and Leak Detection System Water Monitoring and Disposal, Section 10.b. − "Leachate and leak detection water with PCB concentrations from 1 ppm to, but not including, 50 ppm is TSCA reportable material that must be managed in compliance with the ... NPDES Permit." There were no analytical results with ≥1 mg/L (ppm) PCBs for water samples collected from the LCS or LDS during the calendar year and no evidence of hydraulic connection between the layers. Pumped leachate and leak detection liquid were treated by the GWTP.

5. Summary and Review of Water Elevations

The water level above the primary liner (i.e., in the LCS) and the secondary liner (i.e., in the LDS) continued to be measured on a weekly basis throughout 2023. Maximum daily transducer water levels recorded at the LCS and GUS sump are automatically stored at the SCADA system at the GWTP and retrieved by the operator. Tables 2.1, 2.2, and 2.3 show recorded water levels for the LCS, LDS, and GUS, respectively. Table 2.4 presents a summary of the water elevations in each of the sumps. Summaries of the maximum monthly water elevations in each of the systems are presented in Table 2.5. Field data for the LCS, LDS, and GUS are entered directly into electronic forms which are provided as Tables 2.1, 2.2 and 2.3.

Pumping operations began in 2006, with a significant reduction in the average monthly volume of water removed through 2009. Since 2010, the average monthly volume of water removed has generally continued to decline, but at a lessening rate. In July/August 2022, the LCS extubated a sharp temporary increase in the volume of leachate collected. This volume increase was likely a result of an initial influx of leachate collected due to a redistribution of perched water with the fill material that allowed an isolated pocket of leachate to drain to the sump. The fill material continued to dewater into early April 2023. Since 2023, leachate collection volumes have been consistent with the pre-July 2022 volumes. A summary of the average monthly volume of water removed from the LCS and the LDS since 2010 is presented on Figure 5.1 (volume presented is from both the calculation method as used up to 2014 and based on flow meter readings for the LDS to allow for direct comparison between calculation methods and historical monitoring data).

5.1 Leachate Collection System

Manual water level measurements were generally collected on a weekly basis (in excess of the monthly monitoring required by the PCP) in 2023. The automated system records the maximum level and total pumped quantities on a daily basis.

During 2023 the water elevation in the LCS was maintained within the operating limits set out in the PCP. The water levels recorded by the transducers are transmitted through the wireless modem to the PLC. It is these water level readings (converted to elevation) that trigger the pump in the LCS to turn 'on' (set point is 674 feet above mean sea level [AMSL]). On occasion, water level readings recorded at the GWTP are shown as a negative value. The negative water level readings are due to the water level in the sump being below the transducer's 'zero' range. During 2023, manual water levels were monitored as a check on the transducer readings. The depth of water in the LCS was monitored and extracted such that an average level of less than 1-foot of leachate was maintained above the primary liner (over the 7-acre Vault footprint), in accordance with the PCP.

The total amount of water removed from the LCS in 2023 was 35,801 gallons based on flow meter readings, which is less than the estimated 126,114 gallons pumped in 2022.

5.2 Leak Detection System

Pumping at the LDS is conducted via a portable pump discharging through overland hose that is connected to the hard piping within the LCS manhole (for direct discharge to the EQ tank via forcemain). The total amount of water removed from the LDS during the 2023 calendar year was 428 gallons based on flow meter readings.

During 2023, the depth of water in the LDS was maintained such that the water level did not rise more than 18 inches in the sump in accordance with the PCP.

Leakage through the liner is evaluated as an indicator of potential failure of the liner system. Leakage through a liner system can occur through seams and puncture holes from handling and placement or through pinholes inadvertently introduced during the manufacturing process and not visible to the eye. In assessing the potential for leakage through the primary bottom liner system into the LDS, GHD takes records indicating the amount of water collected within the LDS system and compares this volume to a theoretical action leakage rate (ALR) measured in units of

gallons/acre/day (gpad). The volume of water removed (converted to an average flow rate in gpad) should be less than the ALR. The data are used in conjunction with other data to assess the overall performance of the Vault containment system.

The ALR was initially calculated in the Post-Closure Plan (GHD, 25 August 2016), as 32,000 gallons/acre/day (gpad).

The TSCA theoretical ALR for the landfill relative to the actual rate is assessed as an additional line of evidence for the integrity of the Vault liner system.

The equation for calculating the ALR is shown on Page 11 of U.S. EPA's January 1992 Action Leakage Rates for Leak Detection Systems (EPA 530-R-92-004):

$$Q = k * h * \tan(\alpha) * B_{avg}$$

k=1 cm/sec (hydraulic conductivity of INDOT No. 8 stone used in the gravel envelope)

 α =0.0441 (calculated from the elevation difference between the LDS and LCS sumps and the distance between the two along to gravel base, 1.5 ft/34.033072 ft)

D=1 foot (average thickness of the gravel envelope within the LDS)

 $B_{avg}=20$ feet (D/ $sin(\alpha)$)

Based on the above conditions, the ALR is calculated at 18,709 gpad.

The average daily flow rate for 2023 was calculated as the total volume of water removed, divided by the number of days since the previous pumping, divided by the Vault footprint (7 acres). In 2023, 425.7 gallons of water was pumped from January through December 2023 from the LDS. Water was pumped from the LDS system once a month for sample collection purposes. The average daily flow rate was calculated for each month that pumping occurred. The actual action leakage rates were calculated as follows:

Date of Removal	Volume Removed (gallons)	Days Since Last Pumped	Actual Action Leakage Rate (gpad)
January 9, 2023	54.7	34	0.23
February 6, 2023	57.9	27	0.31
March 14, 2023	36.3	35	0.15
April 10, 2023	33.8	26	0.19
May 15, 2023	41.2	34	0.17
June 13, 2023	31.4	28	0.16
July 17, 2023	35	33	0.15
August 7, 2023	36.8	20	0.26
September 11, 2023	36.8	34	0.15
October 12, 2023	26.4	30	0.13
November 9, 2023	19.4	27	0.10
December 7, 2023	16.5	27	0.09

It is concluded that the ALR, using both the original and alternate method outlined above, is higher (including a factor of safety of 2 as suggested by the U.S. EPA in their guidance method) than the quantity of liquid removed from the LDS during 2023, which is suggestive of a liner system which is functioning effectively.

5.3 Gravel Underdrain System

The GUS was installed as part of the overall TSCA Vault construction in order to maintain the stability of the liner system during active operations (e.g., construction and filling of the Vault) by mitigating excessive water pressure action on the bottom liner. Since active filling operations ceased over 10 years ago, the original purpose of the GUS operation is no longer necessary.

Water level measurements were collected by the PLC on a daily basis. The groundwater elevation at the GUS sump remained stable during 2023.

The GUS sump is no longer available as a sampling or extraction point due to obstructions and inoperable pumps within the sump.

6. Issues Encountered and Remedial Actions

No new issues were identified during the reporting period.

In July/August 2022, the LCS exhibited a spike in the volume of leachate collected. This volume increase was likely a result of an initial influx of leachate collected due to a redistribution of perched water within the fill material that allowed an isolated pocket of leachate to drain to the sump. The fill material continued to dewater into early April 2023. Since 2023, leachate collection volumes have been consistent with pre-July 2022 volumes.

7. Spill Cleanup Reports

There were no Facility PCB spills in 2023. There were no spills on public roads.

8. Financial Assurance

As required by the August 2014 RCRA AOC, a surety bond was obtained by GM in 2014 to provide financial assurance for the remaining Corrective Action tasks, including operation and maintenance related to the Vault, until the approval of the Corrective Measures Proposal (CMP); at which time costs to complete Corrective Action will be re-evaluated based on the requirements of the CMP. As required under the AOC, the financial assurance cost estimate is updated, at a minimum, annually. GM provided financial assurance for Fiscal Year 2023 (FY2023) on February 22, 2023. GM submitted the financial assurance cost estimate for FY2024 to U.S. EPA and IDEM on November 16, 2023, with a revised version, based on U.S. EPA comments submitted on February 20, 2024, GM submitted the financial assurance demonstration of the FY2024 financial assurance to U.S. EPA on March 1, 2024. The surety bond in the amount of the approved financial assurance cost estimate remains in effect.

9. References

Conestoga Rovers & Associates. 2012. Post Closure Plan, Bedford Plant Vault, GM CETC Bedford Facility, Bedford Indiana. Ref. No. 13968 (Report 343). February 3.
——. 2016. Post Closure Plan, Bedford Plant Vault, GM CETC Bedford Facility, Bedford, Indiana. Ref. No. 13968 (Report 343 Revision 1). August 25.
GHD. 2023. Memorandum to U.S. EPA. El CA750 Sampling Results First Half 2023. October 11.
——. 2024. Memorandum to U.S. EPA. El CA750 Sampling Results Second Half 2023. January 24.
General Motors LLC. 2023. Letter to U.S. EPA. Progress Report 85, April through September 2023. October 16.
——. 2024. Letter to U.S. EPA. Progress Report 86 October 2023 through March 2024. April 8.

Tables

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water (b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (**) (ft AMSL) *Should not be more than 674.00 ft AMSL*	Water elevation based on transducer manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Jan	-15.4	error					0	Sampled		
2-Jan	-15.4	error					0	Sampled		
3-Jan	-15.4	error					0	Sampled		
4-Jan	-15.4	error	69.19	671.68	error		0	Sampled		
5-Jan	-15.4	error					0	Sampled		
6-Jan	-15.3	error					0	Sampled		
7-Jan	-15.3	error					0	Sampled		
8-Jan	-15.3	error					0	Sampled		
9-Jan	-15.3	error	69.19	671.68	error	770	770	✓ Sampled		sampled and pumped
10-Jan	-15.3	error					770	Sampled		
11-Jan	-15.3	error					770	Sampled		
12-Jan	-15.3	error					770	Sampled		
13-Jan	-15.3	error					770	Sampled		
14-Jan	-15.3	error					770	Sampled		
15-Jan	-15.4	error					770	Sampled		
16-Jan	-15.4	error					770	Sampled		
17-Jan	-15.3	error					770	Sampled		
18-Jan	-15.3	error	69.26	671.61	error		770	Sampled		
19-Jan	-15.3	error					770	Sampled		
20-Jan	-15.3	error					770	Sampled		
21-Jan	-15.3	error					770	Sampled		
22-Jan	-15.3	error					770	Sampled		
23-Jan	-15.3	error	69.24	671.63	error		770	Sampled		
24-Jan	-15.3	error					770	Sampled		
25-Jan	-15.3	error					770	Sampled		
26-Jan	-15.3	error					770	Sampled		
27-Jan	-15.3	error					770	Sampled		
28-Jan	-15.3	error				·	770	Sampled		·
29-Jan	-15.3	error					770	Sampled		
30-Jan	-15.3	error	69.22	671.65	error	·	770	Sampled		
31-Jan	-15.3	error					770	Sampled		
	·					Year to Date Total:	770			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL.

 Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *Should not be more than 674.00 ft AMSL*	Water elevation based on transducer manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Feb	-15.3	error	69.22	671.65	error		0	Sampled		
2-Feb	-15.3	error					0	Sampled		
3-Feb	-15.3	error					0	Sampled		
4-Feb	-15.3	error					0	Sampled		
5-Feb	-15.3	error					0	Sampled		
6-Feb	-15.3	error	69.2	671.67	error	715	715	✓ Sampled		sampled and pumped 69.45 after pumping
7-Feb	-15.3	error					715	Sampled		
8-Feb	-15.3	error					715	Sampled		
9-Feb	-15.3	error					715	Sampled		
10-Feb	-15.3	error					715	Sampled		
11-Feb	-15.3	error					715	Sampled		
12-Feb	-15.3	error					715	Sampled	<u> </u>	
13-Feb	-15.3	error	69.26	671.61	error		715	Sampled		
14-Feb	-15.3	error					715	Sampled	<u> </u>	
15-Feb	-15.3	error					715	Sampled	<u> </u>	
16-Feb	-15.4	error					715	Sampled		
17-Feb	-15.3	error					715	Sampled		
18-Feb	-15.3	error					715	Sampled		
19-Feb	-15.3	error	00.00	671.64			715 715	Sampled		
20-Feb	-15.4	error	69.23	671.64	error		715 715	Sampled	-	
21-Feb 22-Feb	-15.3 -15.3	error					715 715	Sampled		
22-Feb 23-Feb	-15.3 -15.4	error					715 715	Sampled		
23-Feb 24-Feb	-15.4 -15.3	error error					715	Sampled		
25-Feb	-15.3 -15.3	error					715	Sampled		
25-Feb 26-Feb	-15.3 -15.3						715	Sampled		
26-Feb 27-Feb	-15.3 -15.3	error error	69.21	671.66	error		715	Sampled		
28-Feb	-15.3	error	03.21	071.00	enoi		715	Sampled	i i	
20-1-60	-10.0	enoi					710	Sampled		
-										
	ı		l d		I .	Year to Date Total:	1485		l	I .

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL.

 Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 3 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water (b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (**) (ft AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer amanual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Mar	-15.3	error	•			0	0	Sampled		
2-Mar	-15.3	error				0	0	Sampled		
3-Mar	-15.3	error				3175	3175	Sampled		pumped in auto due to rain volume. 2.77" 3/3/23 - 3/4/23
4-Mar	5.6	671.47		-		5215	8390	Sampled		
5-Mar	9.2	671.77				4652	13042	Sampled		
6-Mar	6.3	671.53	67.91	672.96	1.44	0	13042	Sampled		
7-Mar	5.1	671.43				0	13042	Sampled		
8-Mar	5.7	671.48				0	13042	Sampled		
9-Mar	6.4	671.53				0	13042	Sampled		
10-Mar	6	671.50				1188	14230	Sampled		
11-Mar	5	671.42				423	14653	Sampled		
12-Mar	5.3	671.44				0	14653	Sampled		
13-Mar	3.2	671.27	68.09	672.78	1.51	462	15115	Sampled		
14-Mar	2.2	671.18	68.09	672.78	1.60	469	15584	✓ Sampled		sampled and pumped
15-Mar	2.7	671.23				265	15849	Sampled		
16-Mar	4	671.33				0	15849	Sampled		
17-Mar	2.9	671.24				0	15849	Sampled		
18-Mar	2.6	671.22				0	15849	Sampled		
19-Mar	3.3	671.28				0	15849	Sampled		
20-Mar	3.2	671.27	68.07	672.80	1.53	0	15849	Sampled		
21-Mar	3.2	671.27				0	15849	Sampled	<u> </u>	
22-Mar	3.8	671.32				0	15849	Sampled	<u> </u>	
23-Mar	3	671.25				897	16746	Sampled	<u> </u>	
24-Mar	3.8	671.32				26	16772	Sampled	<u> </u>	
25-Mar	3.6	671.30				51	16823	Sampled	<u> </u>	
26-Mar	3.3	671.28			l	581	17404	Sampled		
27-Mar	2.9	671.24	68.11	672.76	1.52	7	17411	Sampled	<u> </u>	
28-Mar	3.7	671.31				141	17552	Sampled	<u> </u>	
29-Mar	3.8	671.32				206	17758	Sampled	<u> </u>	
30-Mar	3.1	671.26			+	0 5695	17758 23453	Sampled	<u> </u>	
31-Mar	4.7	671.39			1	Year to Date Total:	23453 24938	Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Apr	4.9	671.41				3529	3529	Sampled		
2-Apr	2.1	671.18				182	3711	Sampled		
3-Apr	2.4	671.20				3	3714	Sampled		
4-Apr	3	671.25				10	3724	Sampled		
5-Apr	2.7	671.23	68.06	672.81	1.58	0	3724	Sampled		
6-Apr	1.7	671.14				0	3724	Sampled		
7-Apr	2.4	671.20				0	3724	Sampled		
8-Apr	3	671.25				192	3916	Sampled		
9-Apr	2	671.17				0	3916	Sampled		
10-Apr	2.3	671.19	68.06	672.81	1.62	268	4184	✓ Sampled		sampled and ending manual depth 68.11
11-Apr	2.4	671.20				0	4184	Sampled		
12-Apr	2.8	671.23				0	4184	Sampled		
13-Apr	2.5	671.21				0	4184	Sampled		
14-Apr	2.6	671.22				0	4184	Sampled		
15-Apr	2.3	671.19				0	4184	Sampled		
16-Apr	3.2	671.27				0	4184	Sampled		
17-Apr	3.5	671.29				5	4189	Sampled		
18-Apr	2.3	671.19	68.04	672.83	1.64	0	4189	Sampled		
19-Apr	2.4	671.20				0	4189	Sampled		
20-Apr	2.6	671.22				0	4189	Sampled		
21-Apr	2.6	671.22				0	4189	Sampled		
22-Apr	2.6	671.22				0	4189	Sampled		
23-Apr	2.6	671.22				0	4189	Sampled		
24-Apr	2.6	671.22		·		0	4189	Sampled		
25-Apr	2.9	671.24	68.06	672.81	1.57	0	4189	Sampled		
26-Apr	2.7	671.23				0	4189	Sampled		
27-Apr	3.4	671.28				0	4189	Sampled		
28-Apr	3	671.25				0	4189	Sampled		
29-Apr	3.5	671.29				0	4189	Sampled		
30-Apr	3.7	671.31				0	4189	Sampled		
						Year to Date Total:	29127			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL.

 Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 5 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (ht AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-May	3.4	671.28	68	672.87	1.59	0	0	Sampled		
2-May	2.7	671.23				0	0	Sampled		
3-May	2.6	671.22				0	0	Sampled		
4-May	2.7	671.23				0	0	Sampled		
5-May	3.3	671.28				0	0	Sampled		
6-May	3.6	671.30				11	11	Sampled		
7-May	3.8	671.32				0	11	Sampled		
8-May	2.3	671.19				18	29	Sampled		
9-May	2.5	671.21	68.1	672.77	1.56	0	29	Sampled		
10-May	2.7	671.23				42	71	Sampled		
11-May	2.9	671.24				0	71	Sampled	<u> </u>	
12-May	2.9	671.24				0	71	Sampled		
13-May	2.8	671.23				0	71	Sampled		
14-May	2.8	671.23				0	71	Sampled	<u> </u>	
15-May	2.9	671.24	68.01	672.86	1.62	671	742	✓ Sampled	<u> </u>	sampled and collected extra samples for microbial research
16-May	2.6	671.22				0	742	Sampled		
17-May	2.1	671.18				0	742	Sampled	<u> </u>	
18-May	2.1	671.18				0	742	Sampled		
19-May	2.2	671.18				0	742	Sampled		
20-May	2.1	671.18				0	742	Sampled		
21-May	2.2	671.18				0	742	Sampled	<u> </u>	
22-May	2.2	671.18	68.1	672.77	1.59	0	742	Sampled	<u> </u>	
23-May	2.2	671.18				3	745	Sampled	<u> </u>	
24-May	2.2	671.18				0	745	Sampled	<u> </u>	
25-May	2.2	671.18				0	745	Sampled	<u> </u>	
26-May	2.2	671.18				0	745	Sampled	<u> </u>	
27-May	2.3	671.19				0	745	Sampled	<u> </u>	
28-May	2.4	671.20				0	745	Sampled	<u> </u>	
29-May	2.5	671.21	07.00	070.00	4.00	0	745	Sampled		
30-May	2.4	671.20	67.99	672.88	1.68	0	745 745	Sampled	<u> </u>	
31-May	2.5	671.21	1		l .	Year to Date Total:	745 29872	Sampred		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 6 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer t manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Jun	2.4	671.20				0	0	Sampled		
2-Jun	2.6	671.22				0	0	Sampled		
3-Jun	2.6	671.22				70	70	Sampled		
4-Jun	2.5	671.21				26	96	Sampled		
5-Jun	2.8	671.23	68.02	672.85	1.62	0	96	Sampled		
6-Jun	2.6	671.22				0	96	Sampled		
7-Jun	2.8	671.23				0	96	Sampled		
8-Jun	2.6	671.22				0	96	Sampled		
9-Jun	2.8	671.23				0	96	Sampled		
10-Jun	2.8	671.23				0	96	Sampled		
11-Jun	3.4	671.28				0	96	Sampled		
12-Jun	2.3	671.19	68.02	672.85	1.66	0	96	Sampled		
13-Jun	2.5	671.21	67.99	672.88	1.67	342	438	✓ Sampled		
14-Jun	2.3	671.19				0	438	Sampled		
15-Jun	2.3	671.19				0	438	Sampled		
16-Jun	2.3	671.19				0	438	Sampled	~	installed new level sensor
17-Jun	*	*				0	438	Sampled		6/23/23 scheduled to set up and calibrate new level sensor
18-Jun	*	*				0	438	Sampled		
19-Jun	*	*	68.01	672.86	error	0	438	Sampled		
20-Jun	*	*				0	438	Sampled		
21-Jun	*	*		·	The state of the s	0	438	Sampled		
22-Jun	*	*		•		0	438	Sampled		
23-Jun	20.34	672.70	68.12	672.75	0.05	866	1304	Sampled		calibrated level sensor. Reading correctly at LCS not at SCADA
24-Jun	231.0*	231.0*				0	1304	Sampled		SCADA not reading properly
25-Jun	226.0*	226.0*				0	1304	Sampled		
26-Jun	225.7*	225.7*				52	1356	Sampled		
27-Jun	33.4	673.78	68.05	672.82	0.96	0	1356	Sampled	V	SCADA and local are not showing same data
28-Jun	32.8	673.73				0	1356	Sampled		··
29-Jun	28.2	673.35				0	1356	Sampled		
30-Jun	28.6	673.38				0	1356	Sampled		

Year to Date Total: 31228

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin manually pumping. The pumping level manually pumping and the pumping is required but does not automatically begin manually pumping.
- is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.

 (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 7 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (*) (ft AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Jul	27.4	673.28				0	0	Sampled		
2-Jul	27.9	673.33				0	0	Sampled		
3-Jul	28.6	673.38	68.05	672.82	0.56	0	0	Sampled	~	SCADA not reading the same as local readout at LCS 22.37
4-Jul	28.2	673.35				0	0	Sampled	<u> </u>	
5-Jul	28.6	673.38				0	0	Sampled		
6-Jul	28.6	673.38				0	0	Sampled		
7-Jul	28.2	673.35				0	0	Sampled		
8-Jul	28.8	673.40				0	0	Sampled	<u> </u>	
9-Jul	28.9	673.41				0	0	Sampled		
10-Jul	29	673.42	68	672.87	0.55	0	0	Sampled		
11-Jul	28.6	673.38				0	0	Sampled		
12-Jul	28.6	673.38				0	0	Sampled		
13-Jul	28.6	673.38				0	0	Sampled		
14-Jul	28.6	673.38				0	0	Sampled		
15-Jul	28.6	673.38				0	0	Sampled		
16-Jul	28.6	673.38				0	0	Sampled		
17-Jul	28.6	673.38	68.01	672.86	0.52	1105	1105	✓ Sampled		local level readings start 22.37 after pumping 20.34
18-Jul	27.8	673.32				0	1105	Sampled	<u> </u>	
19-Jul	27.4	673.28				0	1105	Sampled		
20-Jul	27.4	673.28				0	1105	Sampled	<u> </u>	
21-Jul	27.4	673.28				0	1105	Sampled		
22-Jul	27.6	673.30				0	1105	Sampled		
23-Jul	27.4	673.28				0	1105	Sampled	<u> </u>	
24-Jul	27.4	673.28	68.11	672.76	0.52	0	1105	Sampled		
25-Jul	28.2	673.35				0	1105	Sampled	<u> </u>	
26-Jul	27.8	673.32				0	1105	Sampled	<u></u> -	
27-Jul	27.8	673.32				0	1105	Sampled		
28-Jul	27.8	673.32				0	1105	Sampled		
29-Jul	28.2	673.35				0	1105	Sampled	<u> </u>	
30-Jul	28.2	673.35			L	0	1105	Sampled		
31-Jul	27.7	673.31	68.1	672.77	0.54	0	1105	Sampled		
						Year to Date Total:	32333			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00

Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 8 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water (b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *Should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Aug	27.8	673.32				0	0	Sampled		
2-Aug	28.1	673.34				0	0	Sampled		
3-Aug	28.1	673.34				0	0	Sampled		
4-Aug	28.5	673.38				0	0	Sampled		
5-Aug	28.6	673.38				0	0	Sampled		
6-Aug	28.6	673.38				0	0	Sampled		
7-Aug	28	673.33	68.07	672.80	0.53	905	905	✓ Sampled		sampled and pumped. 68.24 after pumping
8-Aug	27	673.25				0	905	Sampled	<u> </u>	
9-Aug	27	673.25				0	905	Sampled		
10-Aug	27.4	673.28				0	905	Sampled	<u> </u>	
11-Aug	27.4	673.28				0	905	Sampled	<u> </u>	
12-Aug	27.4	673.28				0	905	Sampled	<u> </u>	
13-Aug	27.8	673.32				0	905	Sampled	<u> </u>	
14-Aug	27.4	673.28				0	905	Sampled		
15-Aug	27	673.25	68.02	672.85	0.40	0	905	Sampled	V	flowmeter calibrations on LCS and GUS/LCS* 150 gallons in simulation mode. No flow.
16-Aug	27	673.25				0	905	Sampled		
17-Aug	27.4	673.28				0	905	Sampled		
18-Aug	27	673.25				0	905	Sampled		
19-Aug	27.4	673.28				0	905	Sampled		
20-Aug	27.8	673.32				0	905	Sampled	<u> </u>	
21-Aug	27.4	673.28	68.14	672.73	0.55	0	905	Sampled		
22-Aug	27.4	673.28				0	905	Sampled	<u> </u>	
23-Aug	28.1	673.34				0	905	Sampled	<u> </u>	
24-Aug	28.1	673.34				0	905	Sampled		
25-Aug	27.8	673.32				0	905	Sampled	<u> </u>	
26-Aug	27.8	673.32				0	905	Sampled	<u> </u>	
27-Aug	27.4	673.28	20.00	070.70	0.50	0	905	Sampled		
28-Aug	27.4	673.28	68.09	672.78	0.50	0	905	Sampled		
29-Aug	27.4	673.28				0	905	Sampled	H	
30-Aug	27.8	673.32				0	905	Sampled		
31-Aug	27.4	673.28				0	905	Sampled		

Year to Date Total: 33238

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin manually upmp ICS. Translated parts of automatically automatica
- is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.

 (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water (b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *Should not be more than 674.00 ft AMSL*	Water elevation based on transducer manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Sep	27.4	673.28				0	0	Sampled		
2-Sep	27.8	673.32				0	0	Sampled		
3-Sep	27.8	673.32				0	0	Sampled		
4-Sep	27.8	673.32				0	0	Sampled		
5-Sep	28.2	673.35	68.09	672.78	0.57	0	0	Sampled		
6-Sep	28.2	673.35				0	0	Sampled		
7-Sep	27.8	673.32				260	260	Sampled		
8-Sep	27.4	673.28				0	260	Sampled		
9-Sep	27.4	673.28				0	260	Sampled		
10-Sep	27.4	673.28				0	260	Sampled		
11-Sep	27.4	673.28	68.09	672.78	0.50	686	946	✓ Sampled		sampled and pumped
12-Sep	26.6	673.22				0	946	Sampled		
13-Sep	26.6	673.22				0	946	Sampled		
14-Sep	26.7	673.23				0	946	Sampled		
15-Sep	26.7	673.23				0	946	Sampled		
16-Sep	27.4	673.28				0	946	Sampled		
17-Sep	26.7	673.23				0	946	Sampled		
18-Sep	26.7	673.23	68.17	672.70	0.52	0	946	Sampled		
19-Sep	27	673.25				0	946	Sampled		
20-Sep	27	673.25				0	946	Sampled		
21-Sep	27	673.25				0	946	Sampled		
22-Sep	27	673.25				0	946	Sampled		
23-Sep	27.4	673.28				0	946	Sampled		
24-Sep	27.4	673.28				0	946	Sampled		
25-Sep	27.4	673.28	68.19	672.68	0.60	0	946	Sampled		
26-Sep	27.8	673.32				0	946	Sampled		
27-Sep	27	673.25				0	946	Sampled		
28-Sep	27.1	673.26				0	946	Sampled		
29-Sep	27	673.25				0	946	Sampled		
30-Sep	27.4	673.28				0	946	Sampled		
						Year to Date Total:	34184			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL.

 Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 10 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (9) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *Should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Oct	28.2	673.35				0	0	Sampled		
2-Oct	27.4	673.28	68.2	672.67	0.61	0	0	Sampled	~	SCADA does not read same as local level sensor
3-Oct	27.4	673.28				0	0	Sampled		
4-Oct	27.4	673.28				0	0	Sampled		
5-Oct	27.6	673.30				0	0	Sampled		
6-Oct	27.6	673.30				0	0	Sampled		
7-Oct	27.8	673.32				0	0	Sampled	<u> </u>	
8-Oct	27.8	673.32				0	0	Sampled		
9-Oct	27.8	673.32				0	0	Sampled		
10-Oct	27.8	673.32				0	0	Sampled	<u> </u>	
11-Oct	27.4	673.28				0	0	Sampled		
12-Oct	27.4	673.28	68.11	672.76	0.52	757	757	✓ Sampled		sampled and pumped
13-Oct	26.6	673.22				0	757	Sampled		
14-Oct	26.7	673.23				0	757	Sampled		
15-Oct	26.7	673.23				0	757	Sampled		
16-Oct	26.7	673.23	68.19	672.68	0.54	0	757	Sampled	<u> </u>	
17-Oct	26.6	673.22				0	757	Sampled		
18-Oct	26.7	673.23				0	757	Sampled	<u> </u>	
19-Oct	27	673.25				0	757	Sampled	<u> </u>	
20-Oct	27	673.25				0	757	Sampled	<u> </u>	
21-Oct	26.6	673.22				0	757	Sampled	<u> </u>	
22-Oct	26.6	673.22	00.40	070.00		0	757	Sampled		
23-Oct	26.6	673.22	68.19	672.68	0.54	0	757	Sampled		
24-Oct	26.6	673.22				0	757	Sampled		
25-Oct	27.4	673.28				0	757	Sampled		
26-Oct	27	673.25				0	757	Sampled		
27-Oct	27 26.3	673.25	68.19	672.68	0.51	0	757 757	Sampled		
28-Oct		673.19	68.19	07∠.08	0.51		757 757	Sampled		
29-Oct	27	673.25				0	757	Sampled		
30-Oct 31-Oct	27 27	673.25 673.25				0	757 757	Sampled		
31-UCT	21	073.25				Year to Date Total:	34941	Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (*) (ft AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Nov	26.6	673.22					0	Sampled		
2-Nov	26.6	673.22					0	Sampled		
3-Nov	26.6	673.22					0	Sampled		
4-Nov	27	673.25					0	Sampled		
5-Nov	27	673.25	68.15	672.72	0.53		0	Sampled	V	SCADA does not match local level reading
6-Nov	27	673.25					0	Sampled		
7-Nov	27.4	673.28					0	Sampled		
8-Nov	27	673.25					0	Sampled		
9-Nov	27	673.25	68.15	672.72	0.53	343	343	✓ Sampled		sampled and pumped
10-Nov	26.6	673.22					343	Sampled		
11-Nov	26.3	673.19					343	Sampled		
12-Nov	27	673.25					343	Sampled		
13-Nov	27	673.25	68.15	672.72	0.53		343	Sampled		
14-Nov	27	673.25					343	Sampled		
15-Nov	27	673.25					343	Sampled		
16-Nov	27	673.25					343	Sampled		
17-Nov	27.4	673.28					343	Sampled		
18-Nov	27.4	673.28					343	Sampled		
19-Nov	27.4	673.28					343	Sampled		
20-Nov	27.4	673.28	68.16	672.71	0.57		343	Sampled		
21-Nov	27	673.25					343	Sampled	<u> </u>	
22-Nov	27	673.25					343	Sampled	<u> </u>	
23-Nov	27	673.25					343	Sampled		
24-Nov	27	673.25					343	Sampled	<u> </u>	
25-Nov	27.4	673.28					343	Sampled	<u> </u>	
26-Nov	27.4	673.28					343	Sampled		
27-Nov	26.6	673.22	68.16	672.71	0.51		343	Sampled		
28-Nov	26.6	673.22					343	Sampled	<u> </u>	
29-Nov	27	673.25					343	Sampled	<u> </u>	
30-Nov	27.4	673.28					343	Sampled		
						Year to Date Total:	35284			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

Table 2.1 Page 12 of 12

2023 Summary of Leachate Collection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Level (a) (from SCADA) (inches) *should not be more than 36 inches*	(1) Calculated Elevation from Transducer Measurement (9) (ft AMSL) *should not be more than 674.00 ft AMSL*	(X) Manual Depth To Water ^(b) (feet) *should not be less than 66.83 ft*	(2) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *should not be more than 674.00 ft AMSL*	Water elevation based on transducer k manual measurement in agreement? (within 6 inches)	Water Pumped (from SCADA) (gallons)	Cumulative Water Removed (gallons)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily		weekly					monthly		
1-Dec	27.4	673.28				0	0	Sampled	~	SCADA does not match local reading
2-Dec	27.4	673.28				0	0	Sampled		
3-Dec	27	673.25				0	0	Sampled	<u> </u>	
4-Dec	27	673.25	68.13	672.74	0.51	0	0	Sampled		
5-Dec	26.6	673.22				0	0	Sampled	<u> </u>	
6-Dec	26.6	673.22				0	0	Sampled		
7-Dec	27.4	673.28	68.08	672.79	0.49	517	517	✓ Sampled		SAMPLED AND PUMPED/ AFTER PUMPED 68.15
8-Dec	27	673.25				0	517	Sampled	<u> </u>	
9-Dec	26.6	673.22				0	517	Sampled	<u> </u>	
10-Dec	26.6	673.22				0	517	Sampled	<u> </u>	
11-Dec	26.6	673.22				0	517	Sampled	<u> </u>	
12-Dec	26.6	673.22				0	517	Sampled		
13-Dec	26.6	673.22				0	517	Sampled		
14-Dec	27.4	673.28				0	517	Sampled		
15-Dec	27.8	673.32				0	517 517	Sampled		
16-Dec	27.4 27	673.28				0	517 517	Sampled		
17-Dec		673.25				-	517	Sampled Sampled		
18-Dec 19-Dec	27 26.6	673.25 673.22				0	517 517	Sampled		
20-Dec	26.6	673.25			ļ	0	517	Sampled		
20-Dec 21-Dec	27	673.25				0	517	Sampled		
21-Dec 22-Dec	27.4	673.28				0	517	Sampled		
22-Dec 23-Dec	27.4	673.28				0	517	Sampled		
24-Dec	27.8	673.32				0	517	Sampled	- i	
25-Dec	27.4	673.28				0	517	Sampled	-	
26-Dec	27.4	673.28				0	517	Sampled	-	
27-Dec	27.2	673.27				0	517	Sampled	-	
28-Dec	27	673.25				0	517	Sampled		
29-Dec	27	673.25				0	517	Sampled		
30-Dec	27.4	673.28				0	517	Sampled		
31-Dec	26.8	673.23				0	517	Sampled		
			1		1	Year to Date Total:	35801		1	I

Notes: Top of sump [top of concrete manhole] (feet AMSL): 740.87 (Oct. 7, 2022) Bottom of sump (feet AMSL): 671.00 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 69.83

- (a) Water level not to rise above 36 inches deep (equates to a water level of 674.00 ft AMSL or 66.83 ft below top of the sump). Pumping must be initiated if the water level is above 674.00 ft AMSL. Pumping automatically initiated based on transducer readings. If does not occur, confirm SCADA water level measurements by taking manual reading. If both transducer and manual readings (converted to elevation) indicate pumping is required but does not automatically begin, manually pump LCS. Troubleshoot lack of automatic pumping.
- (b) Depth to water level should not be less than 66.83 ft below the top of sump (equates to a water level of 674.00 ft AMSL or water depth of 36 inches). Initiate pumping if the water level is above 674.00 ft AMSL. Compare manual water level measurement against transducer reading. Troubleshoot discrepancies.

	(X) Manual Depth To Water ^(a) *should not be less than 71.14 ft* (feet)	(Y) Calculated Elevation from Manual Depth Measurement (**) (ft AMSL) *Should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping	In-Line Flow Meter Reading After Pumping	Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	weekly		(,	,,	,,	,,	,-	AP	monthly		
from previous						0.00	21				
1-Jan							22		Sampled		
2-Jan							23		Sampled		
3-Jan							24		Sampled		
4-Jan	72.81	668.93					25		Sampled		
5-Jan							26		Sampled		
6-Jan							27		Sampled		
7-Jan							28		Sampled		
8-Jan							29		Sampled		
9-Jan	72.81	668.93	72.88	6378	6432	54.7	0		✓ Sampled		sampled and pumped
10-Jan							1		Sampled		
11-Jan							2		Sampled		
12-Jan							3		Sampled		
13-Jan							4		Sampled		
14-Jan							5		Sampled		
15-Jan							6		Sampled		
16-Jan							7		Sampled		
17-Jan							8		Sampled		
18-Jan	72.86	668.88					9		Sampled		
19-Jan							10		Sampled		
20-Jan							11		Sampled		
21-Jan							12		Sampled		
22-Jan							13		Sampled		
23-Jan	72.86	668.88					14		Sampled		
24-Jan							15		Sampled		
25-Jan							16		Sampled		
26-Jan							17		Sampled		
27-Jan							18		Sampled	<u> </u>	
28-Jan							19		Sampled	<u> </u>	
29-Jan							20		Sampled	<u> </u>	
30-Jan	72.88	668.86					21		Sampled	<u> </u>	
31-Jan							22		Sampled		
				Ye	ear to Date Total:	54.7					

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

	(X) Manual Depth To Water ^(a) *should not be less than 71.14 ft* (feet)	(Y) Calculated Elevation from Manual Depth Measurement (9) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping gallons		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	weekly								monthly		
1-Feb							23		Sampled		
2-Feb							24		Sampled		
3-Feb							25		Sampled	<u> </u>	
4-Feb							26		Sampled		
5-Feb		000.00	=0.04	0.100	0.100		27	2.21	Sampled		
6-Feb	72.86	668.88	72.91	6432	6490	57.9	0	0.31	Sampled		sampled and pumped
7-Feb 8-Feb									Sampled		
9-Feb							3		Sampled		
9-Feb 10-Feb							<u>3</u>		Sampled	-	
10-Feb							4 5		Sampled		
12-Feb							<u> </u>		Sampled		
13-Feb	72.9	668.84					7		Sampled		
13-Feb	12.9	000.04					8		Sampled		
15-Feb							9		Sampled		
16-Feb							10		Sampled		
17-Feb							11		Sampled		
18-Feb							12		Sampled		
19-Feb							13		Sampled		
20-Feb	72.89	668.85					14		Sampled		
21-Feb	,00	223.00					15		Sampled		
22-Feb							16		Sampled		
23-Feb							17		Sampled		
24-Feb							18		Sampled		
25-Feb							19		Sampled		
26-Feb							20		Sampled		
27-Feb	72.89	668.85					21		Sampled		
28-Feb							22		Sampled		
	·										
		-					•				
				Ye	ear to Date Total:	112.6					

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022)

Bottom of sump (feet AMSL): 668.50

Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water ^(a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement (*) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping gallons		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Mar	Weekly						23		Sampled		
2-Mar							24		Sampled		
3-Mar							25		Sampled		
4-Mar							26		Sampled	 	
5-Mar							27		Sampled		
6-Mar	72.83	668.91					28		Sampled		
7-Mar							29		Sampled		
8-Mar							30		Sampled		
9-Mar							31		Sampled		
10-Mar							32		Sampled		
11-Mar							33		Sampled		
12-Mar							34		Sampled		
13-Mar	72.93	668.81					35		Sampled		
14-Mar	72.93	668.81	72.93	6490	6526	36.3	0	0.15	✓ Sampled		sampled and pumped
15-Mar							1		Sampled		
16-Mar							2		Sampled		
17-Mar							3		Sampled		
18-Mar							4		Sampled		
19-Mar							5		Sampled		
20-Mar	72.93	668.81					6		Sampled		
21-Mar							7		Sampled		
22-Mar							8		Sampled		
23-Mar							9		Sampled	<u> </u>	
24-Mar							10		Sampled	<u> </u>	
25-Mar							11		Sampled	<u> </u>	
26-Mar							12		Sampled		
27-Mar	72.93	668.81					13		Sampled		
28-Mar							14		Sampled		
29-Mar							15		Sampled		
30-Mar							16		Sampled		
31-Mar			l	.,	ear to Date Total:	148.9	17		Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022)

Inside diameter of sump (feet): 6

Bottom of sump (feet AMSL): 668.50

Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water (a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping gallons			Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Apr	Weekly						18		Sampled		
2-Apr							19		Sampled		
3-Apr							20		Sampled		
4-Apr	72.9	668.84					21		Sampled		
5-Apr							22		Sampled		
6-Apr							23		Sampled		
7-Apr							24		Sampled		
8-Apr							25		Sampled		
9-Apr							26		Sampled		
10-Apr	72.9	668.84	72.94	6526	6560	33.8	0	0.19	Sampled		*not enough water to collect water sample
11-Apr							1		Sampled		
12-Apr							2		Sampled		
13-Apr							3		Sampled		
14-Apr							4		Sampled		
15-Apr							5		Sampled		
16-Apr							6		Sampled		
17-Apr							7		Sampled		
18-Apr	72.92	668.82					8		Sampled	<u> </u>	
19-Apr							9		Sampled	<u> </u>	
20-Apr							10		Sampled		
21-Apr							11		Sampled	<u> </u>	
22-Apr							12	 	Sampled		
23-Apr 24-Apr							13 14	 	Sampled		
24-Apr 25-Apr	72.94	668.80					15		Sampled		
25-Apr 26-Apr	12.94	08.80					16		Sampled		
25-Apr 27-Apr							17	1	Sampled		
28-Apr							18	 	Sampled		
29-Apr							19		Sampled		
30-Apr							20		Sampled		
30-Api							20	 	, , , , , , , , ,		
			1	Ye	ear to Date Total:	182.7		1			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

Pump manually starts based on manual readings

(a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.

(b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

	(X) Manual Depth To Water (a) *should not be less than 71.14 ft* (feet)	(Y) Calculated Elevation from Manual Depth Measurement (**) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	weekly	000.01							monthly		
1-May	72.9	668.84					21		Sampled		
2-May							22		Sampled		
3-May							23		Sampled		
4-May							24		Sampled		
5-May 6-May							25 26		Sampled		
7-May							27		Sampled		
7-iviay 8-Mav							28		Sampled		
	72.96	668.78					28		Sampled		
9-May 10-May	72.96	668.78					30		Sampled		
10-May							31		Sampled		
12-May							32		Sampled		
13-May							33		Sampled		
14-May							34		Sampled		
15-May	72.92	668.82	72	6560	6601	41.2	0	0.17	✓ Sampled		sampled and collected extra microbial research samples
16-May	12.52	008.82	12	0300	0001	41.2	1	0.17	Sampled		Sampled and collected extra microbial research samples
17-May							2		Sampled		
18-May							3		Sampled		
19-May							4		Sampled		
20-May							5		Sampled		
21-May							6		Sampled		
22-May	72.96	668.78					7		Sampled		
23-May	. 2.00	223.70					8		Sampled		
24-May							9		Sampled		
25-May							10		Sampled		
26-May							11	i	Sampled		
27-May							12		Sampled		
28-May							13	i	Sampled		
29-May							14	i	Sampled		
30-May	72.91	668.83					15		Sampled		
31-May							16		Sampled		
			•	Ye	ear to Date Total:	223.9		•		•	

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50

Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water (a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping gallons		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)		Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Jun							17		Sampled		
2-Jun							18		Sampled		
3-Jun							19		Sampled		
4-Jun							20		Sampled		
5-Jun	72.91	668.83					21		Sampled		
6-Jun							22		Sampled		
7-Jun							23		Sampled		
8-Jun							24		Sampled		
9-Jun							25		Sampled		
10-Jun							26		Sampled		
11-Jun							27		Sampled		
12-Jun	72.93	668.81					28		Sampled		
13-Jun	72.93	668.81	73.01	6601	6633	31.4	0	0.16	✓ Sampled		sampled and pumped
14-Jun							11		Sampled		
15-Jun							2		Sampled		
16-Jun							3		Sampled		
17-Jun							4		Sampled	<u> </u>	
18-Jun							5		Sampled	<u> </u>	
19-Jun	72.97	668.77					6		Sampled	<u> </u>	
20-Jun							7		Sampled		
21-Jun							8		Sampled		
22-Jun							9		Sampled		
23-Jun							10 11		Sampled		
24-Jun 25-Jun									Sampled		
25-Jun 26-Jun	72.92	668.82					12 13	-	Sampled		
26-Jun 27-Jun	12.92	008.8∠					13 14		Sampled		
27-Jun 28-Jun							15		Sampled		
28-Jun 29-Jun							16		Sampled		
30-Jun							17		Sampled		
JU-JUII							- 1/		Campled		
				Ve	ear to Date Total:	255.3		l l		1	

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

Pump manually starts based on manual readings

(a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.

(b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water ^(a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement ^(b) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Jul	Weekly						18		Sampled		
2-Jul							19		Sampled		
3-Jul	72.92	668.82					20		Sampled		
4-Jul	72.02	000.02					21		Sampled		
5-Jul							22		Sampled		
6-Jul							23		Sampled		
7-Jul							24		Sampled		
8-Jul							25		Sampled		
9-Jul							26		Sampled		
10-Jul	72.92	668.82					27		Sampled		
11-Jul							28		Sampled		
12-Jul							29		Sampled		
13-Jul							30		Sampled		
14-Jul							31		Sampled		
15-Jul							32		Sampled	<u> </u>	
16-Jul							33		Sampled	<u> </u>	
17-Jul	72.92	668.82	72.95	6633	6667	34.5	0	0.15	Sampled	<u> </u>	sampled and pumped, inflow flowmeter used
18-Jul							1		Sampled	<u> </u>	
19-Jul							2		Sampled	<u> </u>	
20-Jul							3		Sampled	<u> </u>	
21-Jul							4		Sampled	<u> </u>	
22-Jul 23-Jul							<u>5</u>		Sampled	<u> </u>	
23-Jul 24-Jul	72.97	668.77					7		Sampled	<u> </u>	
24-Jul 25-Jul	12.91	008.77					/ 8		Sampled		
25-Jul 26-Jul							9		Sampled		
26-Jul 27-Jul							10		Sampled		
28-Jul							11		Sampled		
29-Jul							12		Sampled		
30-Jul							13		Sampled	— -	
31-Jul	72.95	668.79					14		Sampled		
5. Oui	. 2.00	223.70		Ye	ar to Date Total:	289.8		1			

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

	(X) Manual Depth To Water (a) *should not be less	(Y) Calculated Elevation from Manual Depth Measurement (b) (ft AMSL) *should not be more	(2) Manual Depth To Water After Pumping (if pumping occurred)	In-Line Flow Meter Reading Before Pumping		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
	than 71.14 ft*	than 670.00 ft AMSL*	(feet)	gallons	gallons	gallons	days	gpad			identify issues resolved.
Frequency	weekly								monthly		
1-Aug							15		Sampled		
2-Aug							16		Sampled	<u> </u>	
3-Aug							17		Sampled	 	
4-Aug							18		Sampled	 	
5-Aug							19 20		Sampled		
6-Aug							20		Sampled Sampled		0
7-Aug	72.94	668.80	72.97	6667	6704	36.8	0	0.26	▼ Sampled	V	Sampled and pumped. SCADA does not match local readings this has been presented to Greg W/GHD after new level sensor installed
8-Aug							1		Sampled		
9-Aug							2		Sampled		
10-Aug							3		Sampled		
11-Aug							4		Sampled		
12-Aug							5		Sampled		
13-Aug							6		Sampled	Щ	
14-Aug							7		Sampled	<u> </u>	
15-Aug	72.95	668.79					8		Sampled	<u> </u>	
16-Aug							9		Sampled	<u> </u>	
17-Aug							10		Sampled	<u> </u>	
18-Aug							11		Sampled	<u> </u>	
19-Aug							12		Sampled	H-	
20-Aug	70.05	000.70					13		Sampled	 	
21-Aug 22-Aug	72.95	668.79					14 15		Sampled	 	
22-Aug 23-Aug							15 16	-	Sampled	 	
23-Aug 24-Aug							16 17	-	Sampled	 	
24-Aug 25-Aug							18		Sampled		
26-Aug							19		Sampled	 	
27-Aug							20		Sampled	 	
28-Aug	72.94	668.80					21		Sampled	 	
29-Aug	12.07	000.00					22	1	Sampled	 	
30-Aug							23		Sampled		
31-Aug							24		Sampled		
			ı	Ye	ear to Date Total:	326.6	=÷	ı l			-

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50

Inside diameter of sump (feet): 6 Total depth of sump manhole (feet): 72.64

Pump manually starts based on manual readings

(a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL. (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water (a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement ^(D) (ft AMSL) *Should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping	In-Line Flow Meter Reading After Pumping	Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Sep	Weekly						25		Sampled		
2-Sep							26		Sampled		
3-Sep							27		Sampled		
4-Sep							28		Sampled		
5-Sep	72.94	668.80					29		Sampled		
6-Sep							30		Sampled		
7-Sep							31		Sampled		
8-Sep							32		Sampled		
9-Sep							33		Sampled		
10-Sep							34		Sampled		
11-Sep	72.94	668.80	72.97	6667	6704	36.8	0	0.15	✓ Sampled		sampled and pumped
12-Sep							1		Sampled		
13-Sep							2		Sampled		
14-Sep							3		Sampled		
15-Sep							4		Sampled	<u> </u>	
16-Sep							5		Sampled	<u> </u>	
17-Sep							6		Sampled		
18-Sep	72.97	668.77					7		Sampled		
19-Sep							8		Sampled		
20-Sep							9		Sampled		
21-Sep							10		Sampled	 	
22-Sep							11			 	
23-Sep 24-Sep							12 13		Sampled	 	
24-Sep 25-Sep	72.97	668.77					13 14		Sampled		
25-Sep 26-Sep	12.91	008.77					14 15	-	Sampled		
26-Sep 27-Sep							15 16	1	Sampled		
28-Sep							17		Sampled		
28-Sep 29-Sep							18		Sampled		
29-Sep 30-Sep							19		Sampled		
30-3ep							19		Campied		
			l	Va	ear to Date Total:	363.4		1		1	

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022)

Bottom of sump (feet AMSL): 668.50

Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

Pump manually starts based on manual readings

(a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.

(b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water (a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement (**) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Oct	Wooling						20		Sampled		
2-Oct	73.05	668.69					21		Sampled		
3-Oct	7 0.00	000.00					22		Sampled		
4-Oct							23		Sampled		
5-Oct							24		Sampled		
6-Oct							25		Sampled		
7-Oct							26		Sampled		
8-Oct							27		Sampled		
9-Oct							28		Sampled		
10-Oct	72.95	668.79					29		Sampled		
11-Oct							30		Sampled		
12-Oct	72.95	668.79	72.98	6731	6758	26.4	0	0.13	Sampled	<u> </u>	sampled and pumped
13-Oct							11		Sampled	<u> </u>	
14-Oct							2		Sampled		
15-Oct		000 =0					3		Sampled		
16-Oct 17-Oct	72.98	668.76					<u>4</u> 5		Sampled		
17-Oct 18-Oct									Sampled		
19-Oct							<u>6</u> 7		Sampled		
20-Oct							8		Sampled		
21-Oct							9		Sampled		
22-Oct							10		Sampled		
23-Oct	72.98	668.76					11		Sampled		
24-Oct	. 2.00	223.70					12		Sampled		
25-Oct							13		Sampled		
26-Oct							14		Sampled		
27-Oct							15		Sampled		
28-Oct							16		Sampled		
29-Oct							17		Sampled		
30-Oct	72.98	668.76					18		Sampled		
31-Oct							19		Sampled		
•			·	Ye	ear to Date Total:	389.8	•	·		•	<u> </u>

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Frequency	(X) Manual Depth To Water (a) *should not be less than 71.14 ft* (feet) weekly	(Y) Calculated Elevation from Manual Depth Measurement ^(o) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping	In-Line Flow Meter Reading After Pumping gallons	Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Nov							20		Sampled		
2-Nov							21		Sampled		
3-Nov							22		Sampled		
4-Nov							23		Sampled		
5-Nov							24		Sampled		
6-Nov	72.97	668.77					25		Sampled		
7-Nov							26		Sampled		
8-Nov							27		Sampled		
9-Nov	72.97	668.77	73.3	6758	6777	19.4	0	0.10	✓ Sampled		sampled and pumped
10-Nov							1	ĺ	Sampled		
11-Nov							2	ĺ	Sampled		
12-Nov							3	ĺ	Sampled		
13-Nov	73	668.74					4	ĺ	Sampled		
14-Nov							5		Sampled		
15-Nov							6		Sampled		
16-Nov							7		Sampled		
17-Nov							8		Sampled		
18-Nov							9		Sampled		
19-Nov							10		Sampled		
20-Nov	73.1	668.64					11		Sampled		
21-Nov							12		Sampled		
22-Nov							13		Sampled		
23-Nov							14		Sampled		
24-Nov							15		Sampled		
25-Nov							16		Sampled		
26-Nov							17		Sampled		
27-Nov	73.1	668.64					18		Sampled		
28-Nov							19		Sampled		
29-Nov							20		Sampled	<u> </u>	
30-Nov							21		Sampled		
				Ye	ear to Date Total:	409.2					

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

2023 Summary of Leak Detection System Log East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(X) Manual Depth To Water ^(a) *should not be less than 71.14 ft* (feet)	(Y) Calculated Elevation from Manual Depth Measurement (**) (ft AMSL) *should not be more than 670.00 ft AMSL*	(2) Manual Depth To Water After Pumping (if pumping occurred) (feet)	In-Line Flow Meter Reading Before Pumping gallons		Volume Removed	Days Since Last Pumped	Action Leakage Rate ^(b)	Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	weekly								monthly		
1-Dec							22		Sampled	<u> </u>	
2-Dec							23		Sampled		
3-Dec	70.00	668.76					24 25		Sampled	<u> </u>	
4-Dec 5-Dec	72.98	668.76					25		Sampled		
6-Dec							27		Sampled	 	
7-Dec	72.98	668.76	73.08	6777	6794	16.5	0	0.09	✓ Sampled		*no sample could be taken. Not enough water
8-Dec	12.90	000.76	73.00	0///	6794	16.5	1	0.09	Sampled		no sample could be taken. Not enough water
9-Dec							2		Sampled		
10-Dec							3		Sampled		
11-Dec							4		Sampled		
12-Dec							5		Sampled	 	
13-Dec							6		Sampled		
14-Dec							7		Sampled		
15-Dec							8		Sampled		
16-Dec							9		Sampled		
17-Dec							10		Sampled		
18-Dec							11		Sampled		
19-Dec							12		Sampled		
20-Dec							13		Sampled		
21-Dec							14		Sampled		
22-Dec							15		Sampled		
23-Dec							16		Sampled		
24-Dec							17		Sampled		
25-Dec							18		Sampled		
26-Dec							19		Sampled		
27-Dec							20		Sampled		
28-Dec	-	-					21		Sampled		
29-Dec							22		Sampled		
30-Dec							23		Sampled		
31-Dec							24		Sampled		
				Ye	ear to Date Total:	425.7					

Notes: Top of sump [top of concrete manhole] (feet AMSL): 741.74 (Oct. 7, 2022) Bottom of sump (feet AMSL): 668.50 Inside diameter of sump (feet): 6
Total depth of sump manhole (feet): 72.64

Pump manually starts based on manual readings

- (a) Water level not to rise above 18 inches deep (equates to a water level of 670.00 ft AMSL or 71.14 ft below top of the sump). Pumping must be initiated if the water level is above 670.00 ft AMSL.
- (b) USEPA action leakage rate based on good CQA during construction is 100 gpad. Review operations if calculated ALR is >50 gpad

Table 2.3 Page 1 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
			148000.00					manually entered from last time water pumped in previous year
1-Jan	74.1	668.36	146660.00	-1340.00	-1340	Sampled		
2-Jan	74.1	668.36				Sampled		
3-Jan	74.3	668.37				Sampled		
4-Jan	74.4	668.38				Sampled	<u> </u>	
5-Jan	74.5	668.39				Sampled	<u> </u>	
6-Jan	74.3	668.37				Sampled	<u> </u>	
7-Jan	74.4	668.38				Sampled	<u> </u>	
8-Jan	74.4	668.38				Sampled	<u> </u>	
9-Jan	74.4	668.38				Sampled		
10-Jan	74.7	668.41				Sampled	<u> </u>	
11-Jan	74.6	668.40				Sampled	<u> </u>	
12-Jan	74.5	668.39				Sampled	<u> </u>	
13-Jan	74.6	668.40				Sampled	<u> </u>	
14-Jan	74.4	668.38				Sampled	<u> </u>	
15-Jan	74.6	668.40				Sampled	<u> </u>	
16-Jan	74.6	668.40				Sampled	<u> </u>	
17-Jan	74.5	668.39				Sampled	<u> </u>	
18-Jan	74.5	668.39				Sampled	<u> </u>	
19-Jan	74.6	668.40				Sampled	<u> </u>	
20-Jan	74.7	668.41				Sampled	<u> </u>	
21-Jan	74.4	668.38				Sampled	<u> </u>	
22-Jan	74.4	668.38				Sampled		
23-Jan	74.5	668.39				Sampled	<u> </u>	
24-Jan	74.7	668.41				Sampled		
25-Jan	74.4	668.38				Sampled		
26-Jan	74.6	668.40				Sampled		
27-Jan	74.6	668.40				Sampled	<u> </u>	
28-Jan	74.5	668.39				Sampled		
29-Jan	74.6	668.40				Sampled		
30-Jan	74.6	668.40				Sampled	<u> </u>	
31-Jan	74.4	668.38				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 2 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected monthly	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Feb	74.7	668.41				Sampled		
2-Feb	74.6	668.40				Sampled		
3-Feb	74.6	668.40				Sampled		
4-Feb	74.7	668.41				Sampled		
5-Feb	74.7	668.41				Sampled	<u> </u>	
6-Feb	74.4	668.38				Sampled		
7-Feb	74.4	668.38				Sampled	<u> </u>	
8-Feb	74.4	668.38				Sampled		
9-Feb	74.6	668.40				Sampled	<u> </u>	
10-Feb	74.6	668.40				Sampled	<u> </u>	
11-Feb	74.7	668.41				Sampled	<u> </u>	
12-Feb	74.7	668.41				Sampled	<u> </u>	
13-Feb	74.7	668.41				Sampled	<u> </u>	
14-Feb	74.4	668.38				Sampled	<u> </u>	
15-Feb	74.4	668.38				Sampled	<u> </u>	
16-Feb	74.4	668.38				Sampled	<u> </u>	
17-Feb	74	668.35				Sampled		
18-Feb	74.1	668.36				Sampled		
19-Feb	74	668.35				Sampled	<u> </u>	
20-Feb	74.3	668.37				Sampled	<u> </u>	
21-Feb	72.6	668.23				Sampled	<u> </u>	
22-Feb	72.5	668.22				Sampled	<u> </u>	
23-Feb	72.5	668.22				Sampled	<u> </u>	
24-Feb	72.6	668.23				Sampled	<u> </u>	
25-Feb	72.5	668.22				Sampled	<u> </u>	
26-Feb	72.5	668.22				Sampled	<u> </u>	
27-Feb	72.4	668.21				Sampled	<u> </u>	
28-Feb	72.4	668.21				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 3 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected monthly	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Mar	72.4	668.21				Sampled		
2-Mar	72.4	668.21				Sampled		
3-Mar	72.2	668.20				Sampled		
4-Mar	72.5	668.22				Sampled		
5-Mar	72.5	668.22				Sampled		
6-Mar	72.5	668.22				Sampled		
7-Mar	72.6	668.23				Sampled		
8-Mar	72.8	668.25				Sampled		
9-Mar	72.6	668.23				Sampled		
10-Mar	72.6	668.23				Sampled		
11-Mar	72.5	668.22				Sampled		
12-Mar	72.5	668.22				Sampled		
13-Mar	72.5	668.22				Sampled		
14-Mar	72.2	668.20				Sampled		
15-Mar	72.2	668.20				Sampled		
16-Mar	72.4	668.21				Sampled		
17-Mar	72.6	668.23				Sampled		
18-Mar	72.5	668.22				Sampled		
19-Mar	72.5	668.22				Sampled		
20-Mar	72.6	668.23				Sampled		
21-Mar	72.5	668.22				Sampled		
22-Mar	72.5	668.22				Sampled		
23-Mar	72.4	668.21				Sampled		
24-Mar	72.4	668.21				Sampled		
25-Mar	72.2	668.20				Sampled		
26-Mar	72.4	668.21				Sampled		
27-Mar	72.4	668.21				Sampled		
28-Mar	72.6	668.23				Sampled		
29-Mar	72.4	668.21				Sampled		
30-Mar	72.6	668.23				Sampled	<u> </u>	
31-Mar	72.5	668.22			1	Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 4 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level ^(a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected monthly	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Apr	72.4	668.21				Sampled		
2-Apr	72.4	668.21				Sampled		
3-Apr	72.2	668.20				Sampled		
4-Apr	72.2	668.20				Sampled		
5-Apr	72.5	668.22				Sampled		
6-Apr	72.3	668.21				Sampled		
7-Apr	72.5	668.22				Sampled		
8-Apr	72.6	668.23				Sampled		
9-Apr	72.7	668.24				Sampled		
10-Apr	72.5	668.22				Sampled		
11-Apr	72.5	668.22				Sampled		
12-Apr	72.3	668.21				Sampled		
13-Apr	72.4	668.21				Sampled		
14-Apr	72.4	668.21				Sampled		
15-Apr	72	668.18				Sampled		
16-Apr	72.4	668.21				Sampled		
17-Apr	72.5	668.22				Sampled		
18-Apr	72.4	668.21				Sampled		
19-Apr	72.5	668.22				Sampled		
20-Apr	72.5	668.22				Sampled		
21-Apr	72.1	668.19				Sampled		
22-Apr	72.3	668.21				Sampled		
23-Apr	72.4	668.21				Sampled		
24-Apr	72.1	668.19				Sampled		
25-Apr	71.9	668.17				Sampled		
26-Apr	72.2	668.20				Sampled		
27-Apr	72.2	668.20				Sampled		
28-Apr	72.2	668.20				Sampled		
29-Apr	72.2	668.20				Sampled		
30-Apr	72.2	668.20				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 5 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level ^(a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-May	72.6	668.23				Sampled		
2-May	72	668.18				Sampled		
3-May	71.8	668.16				Sampled		
4-May	71.8	668.16				Sampled		
5-May	71.8	668.16				Sampled		
6-May	71.7	668.16				Sampled		
7-May	71.8	668.16				Sampled		
8-May	72	668.18				Sampled		
9-May	71.8	668.16				Sampled		
10-May	71.8	668.16				Sampled		
11-May	71.9	668.17				Sampled		
12-May	71.9	668.17				Sampled		
13-May	71.8	668.16				Sampled		
14-May	71.8	668.16				Sampled		
15-May	71.9	668.17				Sampled		
16-May	71.8	668.16				Sampled		
17-May	71.7	668.16				Sampled		
18-May	71.9	668.17				Sampled		
19-May	71.8	668.16				Sampled		
20-May	71.8	668.16				Sampled		
21-May	71.5	668.14				Sampled		
22-May	71.5	668.14				Sampled		
23-May	71.8	668.16				Sampled		
24-May	71.6	668.15				Sampled		
25-May	71.6	668.15				Sampled		
26-May	71.6	668.15				Sampled		
27-May	71.4	668.13				Sampled		
28-May	71.6	668.15				Sampled		
29-May	71.2	668.11				Sampled	<u> </u>	
30-May	71.5	668.14				Sampled		
31-May	71.5	668.14				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 6 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Jun	71.5	668.14				Sampled		
2-Jun	71.5	668.14				Sampled		
3-Jun	71.6	668.15				Sampled		
4-Jun	71.8	668.16				Sampled		
5-Jun	71.7	668.16				Sampled		
6-Jun	71.7	668.16				Sampled		
7-Jun	71.7	668.16				Sampled		
8-Jun	71.6	668.15				Sampled		
9-Jun	71.5	668.14				Sampled		
10-Jun	71.5	668.14				Sampled		
11-Jun	71.7	668.16				Sampled		
12-Jun	71.4	668.13				Sampled		
13-Jun	71.9	668.17				Sampled		
14-Jun	71.8	668.16				Sampled		
15-Jun	71.6	668.15				Sampled		
16-Jun	71.6	668.15				Sampled		
17-Jun	71.7	668.16				Sampled		
18-Jun	71.9	668.17				Sampled		
19-Jun	71.9	668.17				Sampled		
20-Jun	72	668.18				Sampled		
21-Jun	71.9	668.17				Sampled		
22-Jun	72	668.18				Sampled		
23-Jun	71.7	668.16				Sampled		
24-Jun	71.8	668.16				Sampled		
25-Jun	71.7	668.16				Sampled		
26-Jun	71.7	668.16				Sampled	<u> </u>	
27-Jun	71.7	668.16				Sampled		
28-Jun	71.9	668.17				Sampled	<u> </u>	
29-Jun	71.6	668.15				Sampled	<u> </u>	
30-Jun	71.9	668.17				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 7 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level ^(a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected monthly	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Jul	71.8	668.16				Sampled		
2-Jul	71.8	668.16				Sampled		
3-Jul	71.8	668.16				Sampled		
4-Jul	71.9	668.17				Sampled		
5-Jul	71.8	668.16				Sampled		
6-Jul	71.7	668.16				Sampled		
7-Jul	71.7	668.16				Sampled		
8-Jul	71.9	668.17				Sampled		
9-Jul	71.9	668.17				Sampled		
10-Jul	71.9	668.17				Sampled		
11-Jul	71.9	668.17				Sampled		
12-Jul	71.9	668.17				Sampled		
13-Jul	71.9	668.17				Sampled		
14-Jul	71.6	668.15				Sampled		
15-Jul	71.6	668.15				Sampled		
16-Jul	71.8	668.16				Sampled		
17-Jul	72.1	668.19				Sampled		
18-Jul	72.1	668.19				Sampled		
19-Jul	72	668.18				Sampled		
20-Jul	72.2	668.20				Sampled	<u> </u>	
21-Jul	72.2	668.20				Sampled		
22-Jul	72.1	668.19				Sampled	<u> </u>	
23-Jul	71.8	668.16				Sampled		
24-Jul	71.8	668.16				Sampled	<u> </u>	
25-Jul	71.9	668.17				Sampled		
26-Jul	72	668.18				Sampled	<u> </u>	
27-Jul	72.2	668.20				Sampled		
28-Jul	72.3	668.21				Sampled	<u> </u>	
29-Jul	72.1	668.19				Sampled		
30-Jul	72.1	668.19				Sampled	<u> </u>	
31-Jul	72	668.18				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 8 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Aug	72.1	668.19				Sampled		
2-Aug	72.1	668.19				Sampled		
3-Aug	72.1	668.19				Sampled		
4-Aug	72	668.18				Sampled		
5-Aug	72	668.18				Sampled		
6-Aug	72	668.18				Sampled		
7-Aug	71.8	668.16				Sampled		
8-Aug	71.8	668.16				Sampled		
9-Aug	72.2	668.20				Sampled		
10-Aug	72	668.18				Sampled		
11-Aug	72	668.18				Sampled		
12-Aug	72	668.18				Sampled		
13-Aug	71.8	668.16				Sampled		
14-Aug	72.1	668.19				Sampled		
15-Aug	72.2	668.20				Sampled	~	Flowmeter calibration on GUS/LCS combined flow
16-Aug	72.1	668.19				Sampled		
17-Aug	71.9	668.17				Sampled		
18-Aug	72	668.18				Sampled		
19-Aug	72	668.18		<u> </u>		Sampled		
20-Aug	72	668.18				Sampled		
21-Aug	72.2	668.20				Sampled		
22-Aug	72	668.18				Sampled		
23-Aug	72	668.18				Sampled		
24-Aug	71.9	668.17				Sampled		
25-Aug	72	668.18				Sampled		
26-Aug	72.1	668.19				Sampled		
27-Aug	72.3	668.21				Sampled		
28-Aug	72.3	668.21				Sampled		
29-Aug	72.2	668.20				Sampled		
30-Aug	72.3	668.21				Sampled	<u> </u>	
31-Aug	72.1	668.19				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 9 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Sep	72.1	668.19				Sampled		
2-Sep	72.1	668.19				Sampled		
3-Sep	72.1	668.19				Sampled		
4-Sep	72	668.18				Sampled		
5-Sep	72.1	668.19				Sampled		
6-Sep	72.2	668.20				Sampled		
7-Sep	72.2	668.20				Sampled		
8-Sep	72	668.18				Sampled		
9-Sep	72	668.18				Sampled		
10-Sep	72	668.18				Sampled		
11-Sep	72	668.18				Sampled		
12-Sep	71.9	668.17				Sampled		
13-Sep	71.9	668.17				Sampled		
14-Sep	72.3	668.21				Sampled		
15-Sep	72.2	668.20				Sampled		
16-Sep	72.3	668.21				Sampled		
17-Sep	72.3	668.21				Sampled		
18-Sep	72.3	668.21				Sampled		
19-Sep	72.1	668.19				Sampled		
20-Sep	72.1	668.19				Sampled		
21-Sep	72	668.18				Sampled		
22-Sep	72.1	668.19				Sampled	<u> </u>	
23-Sep	72	668.18				Sampled		
24-Sep	72	668.18				Sampled	<u> </u>	
25-Sep	72	668.18				Sampled		
26-Sep	72	668.18				Sampled		
27-Sep	71.7	668.16				Sampled		
28-Sep	72.1	668.19				Sampled		
29-Sep	71.9	668.17				Sampled		
30-Sep	71.9	668.17				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 10 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Francisco	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency 1-Oct	71.9	668.17				Sampled		
2-Oct	71.8	668.16				Sampled		
3-Oct	71.8	668.16				Sampled		
4-Oct	72.2	668.20				Sampled		
5-Oct	72.2	668.20				Sampled		
6-Oct	72.2	668.20				Sampled		
7-Oct	72.2	668.20				Sampled		
8-Oct	72.3	668.21				Sampled		
9-Oct	72.3	668.21				Sampled		
10-Oct	72.1	668.19				Sampled		
11-Oct	72.1	668.19				Sampled		
12-Oct	72.1	668.19				Sampled		
13-Oct	72	668.18				Sampled		
14-Oct	72	668.18				Sampled		
15-Oct	72	668.18				Sampled		
16-Oct	72	668.18				Sampled		
17-Oct	72.1	668.19				Sampled		
18-Oct	72.1	668.19				Sampled		
19-Oct	72	668.18		<u> </u>		Sampled		
20-Oct	72.1	668.19				Sampled		
21-Oct	72	668.18				Sampled		
22-Oct	72	668.18				Sampled		
23-Oct	71.7	668.16				Sampled		
24-Oct	71.8	668.16				Sampled	<u> </u>	
25-Oct	72	668.18				Sampled		
26-Oct	72.1	668.19				Sampled	<u> </u>	
27-Oct	71.8	668.16				Sampled	<u> </u>	
28-Oct	72.2	668.20				Sampled	<u> </u>	
29-Oct	72.1	668.19				Sampled	<u> </u>	
30-Oct	72.1	668.19				Sampled	<u> </u>	
31-Oct	72.1	668.19				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 11 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

	(Y) Transducer Water Water Level (a) (from SCADA) (inches) *should not be more than 52 inches*	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
Frequency	daily					monthly		
1-Nov	72	668.18				Sampled	<u> </u>	
2-Nov	72	668.18				Sampled		
3-Nov 4-Nov	72.3 72.3	668.21 668.21				Sampled	 	
5-Nov	72.3	668.18				Sampled		
5-Nov	72	668.18				Sampled		
7-Nov	72.1	668.19				Sampled		
8-Nov	71.8	668.16				Sampled		
9-Nov	71.8	668.16				Sampled		
10-Nov	71.6	668.15				Sampled		
11-Nov	72	668.18				Sampled		
12-Nov	71.7	668.16				Sampled		
13-Nov	71.9	668.17				Sampled		
14-Nov	71.9	668.17				Sampled		
15-Nov	71.8	668.16				Sampled		
16-Nov	71.6	668.15				Sampled		
17-Nov	71.8	668.16				Sampled		
18-Nov	72.1	668.19				Sampled		
19-Nov	72.1	668.19				Sampled		
20-Nov	72.1	668.19				Sampled		
21-Nov	72	668.18	_		_	Sampled		
22-Nov	72	668.18				Sampled		
23-Nov	72	668.18				Sampled		
24-Nov	72.2	668.20				Sampled		
25-Nov	72.2	668.20		<u> </u>		Sampled		
26-Nov	72.1	668.19				Sampled		
27-Nov	71.8	668.16				Sampled		
28-Nov	71.6	668.15				Sampled		
29-Nov	71.9	668.17				Sampled		
30-Nov	71.9	668.17				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Table 2.3 Page 12 of 12

2023 Summary of Gravel Underdrain System Log East Plant Area TCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Frequency	(Y) Transducer Water Water Level ^(a) (from SCADA) (inches) *should not be more than 52 inches* daily	(1) Calculated Elevation from Transducer Measurement (a) (ft AMSL) *should not be more than 666.5 ft AMSL*	Totalizer Reading (from local flow meter) (gallons) *contact GHD to re-do formula if meter is reset	Water Pumped (from local flow meter) (gallons)	Cumulative Water Removed (gallons) (starting Jan. 2023)	Sample Collected	Maintenance, Calibration, or Programing Performed	Comments Summarize issues or observations Provide detail on maintenance, calibration, programing, etc. Identify issues raised to GHD. Identify issues resolved.
1-Dec	72	668.18				Sampled		
2-Dec	71.9	668.17				Sampled		
3-Dec	71.9	668.17				Sampled		
4-Dec	71.9	668.17		<u> </u>		Sampled		
5-Dec	71.9	668.17				Sampled		
6-Dec	71.9	668.17				Sampled		
7-Dec	71.8	668.16				Sampled		
8-Dec	71.8	668.16				Sampled		
9-Dec	71.6	668.15				Sampled		
10-Dec	71.6	668.15				Sampled		
11-Dec	71.6	668.15				Sampled		
12-Dec	71.5	668.14				Sampled		
13-Dec	71.5	668.14				Sampled		
14-Dec	71.7	668.16				Sampled		
15-Dec	71.6	668.15				Sampled		
16-Dec	71.8	668.16				Sampled		
17-Dec	72.1	668.19				Sampled		
18-Dec	71.9	668.17				Sampled		
19-Dec	71.8	668.16				Sampled		
20-Dec	71.8	668.16				Sampled	<u> </u>	
21-Dec	71.8	668.16				Sampled		
22-Dec	71.7	668.16				Sampled	<u> </u>	
23-Dec	71.8	668.16				Sampled		
24-Dec	71.6	668.15				Sampled	<u> </u>	
25-Dec	71.4	668.13				Sampled		
26-Dec	71.6	668.15				Sampled	<u> </u>	
27-Dec	71.6	668.15				Sampled		
28-Dec	71.7	668.16				Sampled		
29-Dec	71.5	668.14				Sampled		
30-Dec	71.4	668.13				Sampled		
31-Dec	71.6	668.15				Sampled		

Notes: Top of sump [top of concrete manhole] (feet AMSL): 738.99 Bottom of sump (feet AMSL): 662.18 Inside diameter of sump (feet): 3
Total depth of sump manhole (feet): 76.81

Pump operating level between 2.5 ft (666.5 ft AMSL) and 3 ft (674.00 ft AMSL or 66.83 ft below the top of sump) of water in the LCS manhole. Pump automatically starts based on transducer reading.

Date (mm/dd/yy)	LCS ⁽¹⁾ Water Elevation (Manual) (ft. AMSL)	LCS ⁽¹⁾ Water Elevation (ft. AMSL)	Lowest Elevation of Primary Liner (ft. AMSL)	LDS ⁽²⁾ Water Elevation (Manual) (ft. AMSL)	Lowest Elevation of Secondary Liner (ft. AMSL)	GUS ⁽³⁾ Water Elevation (PLC) (ft. AMSL)
1/1/23		Not Available ⁽⁴⁾	669.50		667.5	668.36
1/2/23		Not Available (4)	669.50		667.5	668.36
1/3/23		Not Available ⁽⁴⁾	669.50		667.5	668.37
1/4/23	671.68	Not Available (4)	669.50	668.9	667.5	668.38
1/5/23		Not Available ⁽⁴⁾	669.50		667.5	668.39
1/6/23		Not Available (4)	669.50		667.5	668.37
1/7/23		Not Available ⁽⁴⁾	669.50		667.5	668.38
1/8/23		Not Available(4)	669.50		667.5	668.38
1/9/23	671.68	Not Available ⁽⁴⁾	669.50	668.9	667.5	668.38
1/10/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.41
1/11/23		Not Available ⁽⁴⁾	669.50		667.5	668.40
1/12/23	_	Not Available (4)	669.50		667.5	668.39
1/13/23		Not Available ⁽⁴⁾	669.50		667.5	668.40
1/14/23	_	Not Available	669.50		667.5	668.38
1/15/23		Not Available	669.50		667.5	668.40
	I	Not Available				
1/16/23	-	Not Available (4)	669.50		667.5	668.40
1/17/23	-		669.50		667.5	668.39
1/18/23	671.61	Not Available ⁽⁴⁾	669.50	668.9	667.5	668.39
1/19/23		Not Available ⁽⁴⁾	669.50		667.5	668.40
1/20/23		Not Available ⁽⁴⁾	669.50		667.5	668.41
1/21/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.38
1/22/23		Not Available ⁽⁴⁾	669.50		667.5	668.38
1/23/23	671.63	Not Available ⁽⁴⁾	669.50	668.9	667.5	668.39
1/24/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.41
1/25/23		Not Available ⁽⁴⁾	669.50		667.5	668.38
1/26/23		Not Available ⁽⁴⁾	669.50		667.5	668.40
1/27/23		Not Available(4)	669.50		667.5	668.40
1/28/23		Not Available ⁽⁴⁾	669.50		667.5	668.39
1/29/23		Not Available ⁽⁴⁾	669.50		667.5	668.40
1/30/23	671.65	Not Available ⁽⁴⁾	669.50	668.9	667.5	668.40
1/31/23		Not Available (4)	669.50		667.5	668.38
2/1/23	671.65	Not Available ⁽⁴⁾	669.50		667.5	668.41
2/2/23		Not Available	669.50		667.5	668.40
2/3/23		Not Available (4)			667.5	
	I	Not Available (4)	669.50	1		668.40
2/4/23			669.50		667.5	668.41
2/5/23		Not Available ⁽⁴⁾	669.50		667.5	668.41
2/6/23	671.67	Not Available ⁽⁴⁾	669.50	668.9	667.5	668.38
2/7/23		Not Available ⁽⁴⁾	669.50		667.5	668.38
2/8/23		Not Available ⁽⁴⁾	669.50		667.5	668.38
2/9/23		Not Available ⁽⁴⁾	669.50		667.5	668.40
2/10/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.40
2/11/23		Not Available ⁽⁴⁾	669.50		667.5	668.41
2/12/23		Not Available ⁽⁴⁾	669.50		667.5	668.41
2/13/23	671.61	Not Available ⁽⁴⁾	669.50	668.8	667.5	668.41
2/14/23		Not Available ⁽⁴⁾	669.50		667.5	668.38
2/15/23		Not Available (4)	669.50		667.5	668.38
2/16/23		Not Available (4)	669.50		667.5	668.38
2/17/23		Not Available (4)	669.50		667.5	668.35
2/18/23		Not Available ⁽⁴⁾	669.50		667.5	668.36
2/19/23		Not Available ⁽⁴⁾	669.50		667.5	668.35
2/20/23	671.64	Not Available ⁽⁴⁾	669.50	668.9	667.5	668.37
2/21/23		Not Available ⁽⁴⁾	669.50		667.5	668.23
2/22/23		Not Available ⁽⁴⁾	669.50		667.5	668.22
2/23/23		Not Available (4)	669.50		667.5	668.22
2/24/23		Not Available	669.50		667.5	668.23
2/25/23	-	Not Available	669.50		667.5	668.22
2/26/23		Not Available (4)	669.50		667.5	668.22
	I	Not Available (4)				
2/27/23	671.66		669.50	668.9	667.5	668.21
2/28/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.21
3/1/23		Not Available ⁽⁴⁾	669.50		667.5	668.21
3/2/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.21
3/3/23		Not Available ⁽⁴⁾	669.50		667.5	668.20
3/4/23	-	671.47	669.50		667.5	668.22
3/5/23		671.77	669.50	-	667.5	668.22
3/6/23	672.96	671.53	669.50	668.9	667.5	668.22
3/7/23		671.43	669.50		667.5	668.23
3/8/23		671.48	669.50		667.5	668.25
3/9/23		671.53	669.50	-	667.5	668.23
3/10/23		671.5	669.50		667.5	668.23
3/11/23		671.42	669.50		667.5	668.22
3/12/23		671.44	669.50		667.5	668.22
3/13/23	672.78	671.27	669.50	668.8	667.5	668.22
3/14/23	672.78	671.18	669.50	668.8	667.5	668.20
3/15/23		671.23	669.50		667.5	668.20
0/10/20				1	667.5	
3/16/23		671.33	669.50			668.21

Date (mm/dd/yy)	LCS ⁽¹⁾ Water Elevation (Manual) (ft. AMSL)	LCS ⁽¹⁾ Water Elevation (ft. AMSL)	Lowest Elevation of Primary Liner (ft. AMSL)	LDS ⁽²⁾ Water Elevation (Manual) (ft. AMSL)	Lowest Elevation of Secondary Liner (ft. AMSL)	GUS ⁽³⁾ Water Elevation (PLC (ft. AMSL)
3/18/23	<u> </u>	671.22	669.50		667.5	668.22
3/19/23		671.28	669.50		667.5	668.22
				1		
3/20/23	672.80	671.27	669.50	668.8	667.5	668.23
3/21/23	-	671.27	669.50		667.5	668.22
3/22/23	-	671.32	669.50		667.5	668.22
3/23/23		671.25	669.50		667.5	668.21
3/24/23	-	671.32	669.50		667.5	668.21
3/25/23		671.3	669.50		667.5	668.20
3/26/23		671.28	669.50		667.5	668.21
3/27/23	672.76	671.24	669.50	668.8	667.5	668.21
				1		
3/28/23		671.31	669.50	-	667.5	668.23
3/29/23	-	671.32	669.50		667.5	668.21
3/30/23	-	671.26	669.50		667.5	668.23
3/31/23		671.4	669.50		667.5	668.22
4/1/23		671.4	669.50		667.5	668.21
4/2/23		671.18	669.50		667.5	668.21
				1		
4/3/23	-	671.2	669.50		667.5	668.20
4/4/23	-	671.25	669.50	668.8	667.5	668.20
4/5/23	672.81	671.23	669.50		667.5	668.22
4/6/23		671.14	669.50		667.5	668.21
4/7/23		671.2	669.50		667.5	668.22
4/8/23		671.25	669.50		667.5	668.23
4/9/23				1		
		671.17	669.50		667.5	668.24
4/10/23	672.81	671.19	669.50	668.8	667.5	668.22
4/11/23		671.2	669.50		667.5	668.22
4/12/23		671.23	669.50		667.5	668.21
4/13/23		671.21	669.50		667.5	668.21
4/14/23		671.22	669.50		667.5	
				-		668.21
4/15/23	-	671.19	669.50		667.5	668.18
4/16/23	-	671.27	669.50		667.5	668.21
4/17/23		671.29	669.50		667.5	668.22
4/18/23	672.83	671.19	669.50	668.8	667.5	668.21
4/19/23		671.2	669.50		667.5	668.22
4/20/23		671.22	669.50		667.5	668.22
4/21/23		671.22	669.50		667.5	668.19
4/22/23	-	671.22	669.50		667.5	668.21
4/23/23		671.22	669.50		667.5	668.21
4/24/23		671.22	669.50		667.5	668.19
4/25/23	672.81	671.24	669.50	668.8	667.5	668.17
4/26/23		671.23	669.50		667.5	668.20
4/27/23	-	671.28	669.50		667.5	668.20
4/28/23		671.25	669.50		667.5	668.20
4/29/23		671.29	669.50		667.5	668.20
4/30/23	-	671.31	669.50		667.5	668.20
5/1/23	672.87	671.3	669.50	668.8	667.5	668.23
5/2/23		671.23	669.50		667.5	668.18
				1		
5/3/23	-	671.22	669.50		667.5	668.16
5/4/23		671.23	669.50		667.5	668.16
5/5/23		671.28	669.50		667.5	668.16
5/6/23		671.3	669.50		667.5	668.16
5/7/23		671.32	669.50		667.5	668.16
5/8/23		671.19	669.50		667.5	668.18
5/9/23	672.77	671.21	669.50	668.8	667.5	668.16
	072.77			000.0	I I	
5/10/23	I	671.23	669.50		667.5	668.16
5/11/23	-	671.24	669.50		667.5	668.17
5/12/23		671.24	669.50		667.5	668.17
5/13/23	-	671.23	669.50		667.5	668.16
5/14/23		671.23	669.50		667.5	668.16
5/15/23	672.86	671.24	669.50	668.8	667.5	668.17
5/16/23		671.22	669.50	-	667.5	668.16
5/17/23		671.18	669.50		667.5	668.16
5/18/23		671.18	669.50		667.5	668.17
5/19/23		671.18	669.50		667.5	668.16
5/20/23		671.18	669.50		667.5	668.16
5/21/23		671.18	669.50		667.5	668.14
5/22/23	672.77	671.18	669.50	668.8	667.5	668.14
5/23/23	-	671.18	669.50		667.5	668.16
5/24/23		671.18	669.50		667.5	668.15
5/25/23		671.18	669.50		667.5	668.15
5/26/23		671.18	669.50		667.5	668.15
5/27/23		671.19	669.50		667.5	668.13
				1		
5/28/23	-	671.2	669.50		667.5	668.15
5/29/23	-	671.21	669.50	-	667.5	668.11
5/30/23	672.88	671.2	669.50	668.8	667.5	668.14
5/31/23		671.21	669.50		667.5	668.14
3/3/1/23						

Date (mm/dd/yy)	LCS ⁽¹⁾ Water Elevation (Manual) (ft. AMSL)	LCS ⁽¹⁾ Water Elevation (ft. AMSL)	Lowest Elevation of Primary Liner (ft. AMSL)	LDS ⁽²⁾ Water Elevation (Manual) (ft. AMSL)	Lowest Elevation of Secondary Liner (ft. AMSL)	GUS ⁽³⁾ Water Elevation (PLC (ft. AMSL)
6/2/23		671.22	669.50		667.5	668.14
6/3/23		671.22	669.50		667.5	668.15
6/4/23		671.21	669.50		667.5	668.16
6/5/23	672.85	671.23	669.50	668.8	667.5	668.16
6/6/23		671.22	669.50		667.5	668.16
6/7/23		671.23	669.50		667.5	668.16
6/8/23		671.22	669.50		667.5	668.15
6/9/23		671.23	669.50	-	667.5	668.14
6/10/23		671.23	669.50		667.5	668.14
6/11/23		671.28	669.50		667.5	668.16
6/12/23	672.85	671.19	669.50	668.8	667.5	668.13
6/13/23	672.88	671.21	669.50	668.8	667.5	668.17
6/14/23		671.19	669.50		667.5	668.16
6/15/23		671.19	669.50		667.5	668.15
6/16/23		671.19	669.50		667.5	668.15
6/17/23		Not Available (4)	669.50		667.5	668.16
6/18/23		Not Available ⁽⁴⁾	669.50		667.5	668.17
		Not Available				
6/19/23	672.86		669.50	668.8	667.5	668.17
6/20/23	-	Not Available ⁽⁴⁾	669.50		667.5	668.18
6/21/23		Not Available ⁽⁴⁾	669.50		667.5	668.17
6/22/23	-	Not Available (4)	669.50		667.5	668.18
6/23/23	672.75	672.7	669.50		667.5	668.16
6/24/23		231.0	669.50		667.5	668.16
6/25/23		226.0	669.50		667.5	668.16
6/26/23		225.7	669.50	668.8	667.5	668.16
6/27/23	672.82	673.8	669.50		667.5	668.16
	072.02					668.17
6/28/23		673.7	669.50		667.5	
6/29/23		673.4	669.50	-	667.5	668.15
6/30/23	-	673.4	669.50		667.5	668.17
7/1/23	-	673.28	669.50		667.5	668.16
7/2/23		673.33	669.50		667.5	668.16
7/3/23	672.82	673.38	669.50	668.8	667.5	668.16
7/4/23		673.35	669.50		667.5	668.17
7/5/23		673.38	669.50		667.5	668.16
7/6/23		673.38	669.50		667.5	668.16
7/7/23		673.35	669.50		667.5	668.16
	-					
7/8/23		673.4	669.50		667.5	668.17
7/9/23		673.41	669.50		667.5	668.17
7/10/23	672.87	673.42	669.50	668.8	667.5	668.17
7/11/23		673.38	669.50		667.5	668.17
7/12/23		673.38	669.50		667.5	668.17
7/13/23		673.38	669.50		667.5	668.17
7/14/23		673.38	669.50		667.5	668.15
7/15/23		673.38	669.50		667.5	668.15
7/16/23		673.38	669.50		667.5	668.16
				668.8		
7/17/23	672.86	673.38	669.50		667.5	668.19
7/18/23		673.32	669.50		667.5	668.19
7/19/23		673.28	669.50		667.5	668.18
7/20/23	-	673.28	669.50		667.5	668.20
7/21/23	-	673.28	669.50		667.5	668.20
7/22/23		673.3	669.50		667.5	668.19
7/23/23		673.28	669.50		667.5	668.16
7/24/23	672.76	673.28	669.50	668.8	667.5	668.16
7/25/23		673.35	669.50		667.5	668.17
7/26/23		673.32	669.50		667.5	668.18
7/27/23	_	673.32	669.50			
	-				667.5	668.20
7/28/23	-	673.32	669.50		667.5	668.21
7/29/23		673.35	669.50		667.5	668.19
7/30/23	-	673.35	669.50		667.5	668.19
7/31/23	672.77	673.31	669.50	668.8	667.5	668.18
8/1/23		673.32	669.50		667.5	668.19
8/2/23	_	673.34	669.50		667.5	668.19
8/3/23		673.34	669.50		667.5	668.19
8/4/23		673.38	669.50		667.5	668.18
8/5/23	_	673.38	669.50			
					667.5	668.18
8/6/23		673.38	669.50		667.5	668.18
8/7/23	672.80	673.33	669.50	668.8	667.5	668.16
8/8/23	-	673.25	669.50		667.5	668.16
8/9/23	-	673.25	669.50		667.5	668.20
8/10/23		673.28	669.50		667.5	668.18
8/11/23		673.28	669.50		667.5	668.18
8/12/23		673.28	669.50			668.18
	-				667.5	
8/13/23		673.32	669.50		667.5	668.16
8/14/23		673.28	669.50		667.5	668.19
8/15/23	672.85	673.25	669.50	668.8	667.5	668.20
8/16/23		673.25	669.50		667.5	668.19

Date (mm/dd/yy)	LCS ⁽¹⁾ Water Elevation (Manual) (ft. AMSL)	LCS ⁽¹⁾ Water Elevation (ft. AMSL)	Lowest Elevation of Primary Liner (ft. AMSL)	LDS ⁽²⁾ Water Elevation (Manual) (ft. AMSL)	Lowest Elevation of Secondary Liner (ft. AMSL)	GUS ⁽³⁾ Water Elevation (PLC) (ft. AMSL)
8/17/23		673.28	669.50		667.5	668.17
8/18/23		673.25	669.50		667.5	668.18
8/19/23		673.28	669.50		667.5	668.18
8/20/23		673.32	669.50		667.5	668.18
8/21/23	672.73	673.28	669.50	668.8	667.5	668.20
8/22/23	-	673.28	669.50		667.5	668.18
8/23/23		673.34	669.50		667.5	668.18
				1		
8/24/23		673.34	669.50		667.5	668.17
8/25/23		673.32	669.50		667.5	668.18
8/26/23	-	673.32	669.50		667.5	668.19
8/27/23	-	673.28	669.50		667.5	668.21
8/28/23	672.78	673.28	669.50	668.8	667.5	668.21
8/29/23		673.28	669.50		667.5	668.20
8/30/23		673.32	669.50		667.5	668.21
8/31/23		673.28	669.50		667.5	668.19
9/1/23		673.28	669.50		667.5	668.19
				1		
9/2/23		673.32	669.50		667.5	668.19
9/3/23	-	673.32	669.50		667.5	668.19
9/4/23	-	673.32	669.50		667.5	668.18
9/5/23	672.78	673.35	669.50	668.8	667.5	668.19
9/6/23		673.35	669.50		667.5	668.20
9/7/23		673.32	669.50		667.5	668.20
9/8/23		673.28	669.50		667.5	668.18
		673.28		1		
9/9/23	-		669.50		667.5	668.18
9/10/23		673.28	669.50		667.5	668.18
9/11/23	672.78	673.28	669.50	668.8	667.5	668.18
9/12/23		673.22	669.50		667.5	668.17
9/13/23		673.22	669.50		667.5	668.17
9/14/23		673.23	669.50		667.5	668.21
9/15/23		673.23	669.50		667.5	668.20
9/16/23		673.28	669.50		667.5	668.21
9/17/23		673.23	669.50		667.5	668.21
9/18/23	672.70	673.23	669.50	668.8	667.5	668.21
9/19/23	-	673.25	669.50		667.5	668.19
9/20/23		673.25	669.50		667.5	668.19
9/21/23		673.25	669.50		667.5	668.18
9/22/23		673.25	669.50		667.5	668.19
9/23/23		673.28	669.50		667.5	668.18
9/24/23		673.28	669.50		667.5	668.18
9/25/23	672.68	673.28	669.50	668.8	667.5	668.18
				1		
9/26/23		673.32	669.50		667.5	668.18
9/27/23		673.25	669.50		667.5	668.16
9/28/23	-	673.26	669.50		667.5	668.19
9/29/23		673.25	669.50		667.5	668.17
9/30/23		673.28	669.50		667.5	668.17
10/1/23		673.35	669.50		667.5	668.17
10/2/23	672.67	673.28	669.50	668.7	667.5	668.16
10/3/23		673.28	669.50		667.5	668.16
	-					
10/4/23		673.28	669.50		667.5	668.20
10/5/23		673.3	669.50		667.5	668.20
10/6/23	-	673.3	669.50		667.5	668.20
10/7/23		673.32	669.50		667.5	668.20
10/8/23		673.32	669.50		667.5	668.21
10/9/23		673.32	669.50		667.5	668.21
10/10/23		673.32	669.50	668.8	667.5	668.19
10/11/23		673.28	669.50		667.5	668.19
				1		
10/12/23	672.76	673.28	669.50	668.8	667.5	668.19
10/13/23		673.22	669.50		667.5	668.18
10/14/23		673.23	669.50		667.5	668.18
10/15/23		673.23	669.50		667.5	668.18
10/16/23	672.68	673.23	669.50	668.8	667.5	668.18
10/17/23		673.22	669.50		667.5	668.19
10/18/23		673.23	669.50		667.5	668.19
10/19/23		673.25	669.50			668.18
					667.5	
10/20/23		673.25	669.50		667.5	668.19
10/21/23		673.22	669.50		667.5	668.18
10/22/23		673.22	669.50		667.5	668.18
10/23/23	672.68	673.22	669.50	668.8	667.5	668.16
10/24/23		673.22	669.50		667.5	668.16
10/25/23		673.28	669.50		667.5	668.18
10/26/23		673.25	669.50		667.5	668.19
10/27/23		673.25	669.50		667.5	668.16
10/28/23	672.68	673.19	669.50		667.5	668.20
10/29/23		673.25	669.50		667.5	668.19
10/30/23		673.25	669.50	668.8	667.5	668.19
10/30/23						

Date (mm/dd/yy)			Lowest Elevation of Primary Liner (ft. AMSL)	LDS ⁽²⁾ Water Elevation (Manual) (ft. AMSL)	Lowest Elevation of Secondary Liner (ft. AMSL)	GUS ⁽³⁾ Water Elevation (PLC (ft. AMSL)
11/1/23		673.22	669.50		667.5	668.18
11/2/23		673.22	669.50		667.5	668.18
11/3/23		673.22	669.50		667.5	668.21
11/4/23		673.25	669.50		667.5	668.21
11/5/23	672.72	673.25	669.50		667.5	668.18
	012.12	673.25				
11/6/23	-		669.50	668.8	667.5	668.18
11/7/23		673.28	669.50		667.5	668.19
11/8/23		673.25	669.50		667.5	668.16
11/9/23	672.72	673.25	669.50	668.8	667.5	668.16
11/10/23		673.22	669.50		667.5	668.15
11/11/23		673.19	669.50		667.5	668.18
11/12/23		673.25	669.50		667.5	668.16
11/13/23	672.72	673.25	669.50	668.7	667.5	668.17
11/14/23		673.25	669.50		667.5	668.17
11/15/23		673.25	669.50		667.5	668.16
		673.25				
11/16/23			669.50		667.5	668.15
11/17/23		673.28	669.50		667.5	668.16
11/18/23		673.28	669.50		667.5	668.19
11/19/23		673.28	669.50		667.5	668.19
11/20/23	672.71	673.28	669.50	668.6	667.5	668.19
11/21/23		673.25	669.50		667.5	668.18
11/22/23		673.25	669.50		667.5	668.18
11/23/23		673.25	669.50		667.5	668.18
11/24/23		673.25	669.50		667.5	668.20
11/25/23	-	673.28	669.50		667.5	668.20
		673.28				
11/26/23			669.50		667.5	668.19
11/27/23	672.71	673.22	669.50	668.6	667.5	668.16
11/28/23		673.22	669.50		667.5	668.15
11/29/23		673.25	669.50		667.5	668.17
11/30/23		673.28	669.50		667.5	668.17
12/1/23		673.28	669.50		667.5	668.18
12/2/23		673.28	669.50		667.5	668.17
12/3/23		673.25	669.50		667.5	668.17
12/4/23	672.74	673.25	669.50	668.8	667.5	668.17
12/5/23		673.22	669.50		667.5	668.17
12/6/23		673.22	669.50		667.5	668.17
12/7/23	672.79	673.28	669.50	668.8	667.5	668.16
12/8/23		673.25	669.50		667.5	668.16
12/9/23		673.22	669.50		667.5	668.15
12/10/23		673.22	669.50		667.5	668.15
12/11/23		673.22	669.50		667.5	668.15
12/12/23		673.22	669.50		667.5	668.14
12/13/23		673.22	669.50		667.5	668.14
12/14/23		673.28	669.50		667.5	668.16
12/15/23		673.32	669.50		667.5	668.15
		673.28				
12/16/23			669.50	1	667.5	668.16
12/17/23		673.25	669.50		667.5	668.19
12/18/23		673.25	669.50		667.5	668.17
12/19/23		673.22	669.50		667.5	668.16
12/20/23		673.25	669.50		667.5	668.16
12/21/23		673.25	669.50		667.5	668.16
12/22/23		673.28	669.50		667.5	668.16
12/23/23		673.28	669.50		667.5	668.16
12/24/23		673.32	669.50		667.5	668.15
		673.28			667.5	
12/25/23			669.50			668.13
12/26/23		673.28	669.50		667.5	668.15
12/27/23		673.27	669.50		667.5	668.15
12/28/23		673.25	669.50		667.5	668.16
12/29/23		673.25	669.50		667.5	668.14
12/30/23		673.28	669.50		667.5	668.13
12/31/23	I	673.23	669.50	1	667.5	668.15

Notes:

AMSL - Above mean sea level

ft - feet

LCS: Top of 6-ft. diameter sump [top of concrete manhole] (feet AMSL): 740.83, Bottom of sump (feet AMSL): 671.00, Total depth of sump manhole (feet): 69.83.

² LDS: Top of 6-ft. diameter sump [top of concrete manhole] (feet AMSL): 741.14, Bottom of sump (feet AMSL): 668.5, Total depth of sump manhole (feet): 72.64 Top of concrete manhole where water levels readings are collected re-surveyed October 7, 2022: 741.74 (ft. AMSL)

³ GUS: Top of 3-ft diameter sump [top of concrete] (feet AMSL): 738.99, Bottom of sump (feet AMSL): 662.18, Total depth of sump manhole (feet): 76.81.

The error reading on the LCS transducer is a result of the leachate level being below what the transducer recognizes as "zero." Therefore, no reading is available. On June 23, 2024 the level sensor was calibrated. The LCS was reading correct but not the SCADA.

Table 2.5

2023 LCS, LDS, and GUS Maximum Water Elevation Summary East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Date	LCS ¹	LCS ¹	LDS ²	LDS ²	GUS ³	GUS ³
Operational Leve	Manual Recorded Depth to Water (ft.)	Max. Water Surface Elevation (manual) (ft. AMSL)	Manual Recorded Depth to Water (ft.)	Max. Water Surface Elevation (manual) (ft. AMSL)	PLC-Recorded Water Depth (inches)	Max. Water Surface Elevation (PLC) (ft AMSL)
Jan-23	69.19	671.64	72.81	668.33	74.7	674.81
Feb-23	69.20	671.63	72.86	668.28	74.7	674.81
Mar-23	67.91	672.92	72.83	668.31	72.6	674.63
Apr-23	68.04	672.79	72.90	668.24	72.7	674.64
May-23	67.99	672.84	72.90	668.24	72.6	674.63
Jun-23	67.99	672.84	72.91	668.23	72	674.58
Jul-23	68	672.83	72.92	668.22	72.3	674.61
Aug-23	68.02	672.81	72.94	668.20	72.3	674.61
Sep-23	68.09	672.74	72.94	668.20	72.3	674.61
Oct-23	68.11	672.72	72.95	668.79	72.3	674.61
Nov-23	68.15	672.68	72.97	668.77	72.3	674.61
Dec-23	68.08	672.75	72.98	668.76	72.1	674.59

Notes:

AMSL - Above mean sea level

ft - feet

Indication of water level reaching or exceeding the operational limit.

¹ LCS: Top of 6-ft. diameter sump [top of concrete manhole] (feet AMSL): 740.83, Bottom of sump (feet AMSL): 671.00, Total depth of sump manhole (feet): 69.83. Pump operating start level: 674.00 ft. AMSL

² LDS: Top of 6-ft. diameter sump [top of concrete manhole] (feet AMSL): 741.14, Bottom of sump (feet AMSL): 668.5, Total depth of sump manhole (feet): 72.64

Top of concrete manhole where water levels readings are collected re-surveyed October 7, 2022: 741.74 (ft. AMSL). Operating start level: 670.00

Pump operating start level: 670.00 ft. AMSL. Water elevation that exceeds 1 ft over primary liner: 671.5 ft. AMSL

³ GUS: Top of 3-ft diameter sump [top of concrete] (feet AMSL): 738.99, Bottom of sump (feet AMSL): 662.18, Total depth of sump manhole (feet): 76.81.

Pump operating start level: 666.5 ft. AMSL

Table 2.6

2023 Summary of Monthly Total Volume of Water Treated East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Month	Groundwater Treatment Plant (GWTP) Number of Operational Days	Volume of Water Treated/Discharged at the GWTP (million gallons)	Daily Average Water Treated/Discharged at the GWTP (million gallons)
Jan-23	31	3.356	0.108
Feb-23	28	2.626	0.094
Mar-23	31	3.917	0.126
Apr-23	30	2.760	0.092
May-23	31	1.038	0.033
Jun-23	30	0.872	0.029
Jul-23	31	3.743	0.121
Aug-23	31	2.083	0.067
Sep-23	30	0.887	0.030
Oct-23	31	0.692	0.022
Nov-23	30	0.81	0.027
Dec-23	31	1.083	0.035
Total	365	23.867	
Month Average	-	1.989	
Daily Average	-	0.065	

Table 3.1

Sample Location Sample Date Parameters	Units	9-4 05/24/2023	CH-20 05/24/2023	CH-42 05/22/2023	CH-42A 05/22/2023	CH-43 05/22/2023	CH-44 05/22/2023	MW-X033Y147S 05/25/2023	MW-X043Y176 05/23/2023	MW-X047Y236 05/23/2023	MW-X085Y070S-1 05/25/2023	MW-X085Y070S-2 05/25/2023	MW-X146Y084 05/24/2023	MW-X146Y084 05/24/2023	MW-X169Y058S-1 05/25/2023	MW-X227Y054 05/23/2023	MW-X242Y060S 05/24/2023
Polychlorinated biphenyl (PCBs)																	
Aroclor-1016 (PCB-1016) Aroclor-1221 (PCB-1221) Aroclor-1232 (PCB-1232) Aroclor-1242 (PCB-1242) Aroclor-1248 (PCB-1248) Aroclor-1254 (PCB-1254) Aroclor-1260 (PCB-1260) Total PCBs	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	0.11 U 0.11 U 0.11 U 0.33 0.11 U 0.11 U 0.11 U 0.33	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U ND	0.10 U 0.10 U 0.10 U 0.15 0.10 U 0.10 U 0.10 U 0.15	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.099 U 0.099 U 0.099 U 0.099 U 0.099 U 0.099 U 0.099 U ND	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U ND	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	2.0 U 2.0 U 2.0 U 24 2.0 U 2.0 U 2.0 U 24	48 U 48 U 48 U 130 48 U 48 U 48 U 130
Aroclor-1016 (PCB-1016) (dissolved) Aroclor-1221 (PCB-1221) (dissolved) Aroclor-1232 (PCB-1232) (dissolved) Aroclor-1242 (PCB-1242) (dissolved) Aroclor-1248 (PCB-1248) (dissolved) Aroclor-1254 (PCB-1254) (dissolved) Aroclor-1260 (PCB-1260) (dissolved) Total PCBs (dissolved)	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	0.099 U 0.099 U 0.099 U 0.099 U 0.099 U 0.099 U 0.099 U	0.12 U 0.12 U 0.12 U 0.12 U 0.12 U 0.12 U 0.12 U 0.12 U	0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.099 U 0.099 U 0.099 U 0.099 U 0.099 U 0.099 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.10 U 0.10 U 0.10 U 0.49 0.10 U 0.10 U 0.10 U 0.49
Semi-Volatile Organic Compounds (SVOCs)																	
2,2'-Oxybis(1-chloropropane) (bis(2-Chloroisopropyl) ether) 2,4,5-Trichlorophenol 2,4,6-Trichlorophenol 2,4-Dinethylphenol 2,4-Dinitrophenol 2,4-Dinitrophenol 2,4-Dinitrotoluene 2,6-Dinitrotoluene 2,6-Dinitrotoluene 2-Chlorophenol 2-Methylnaphthalene 2-Methylphenol 2-Methylphenol 2-Nitroaniline 2-Nitrophenol 3&4-Methylphenol 3,3'-Dichlorobenzidine 3-Nitroaniline 4,6-Dinitro-2-methylphenol 4-Bromophenyl phenyl ether 4-Chloro-3-methylphenol 4-Chloro-3-methylphenol 4-Chloro-3-methylphenol 4-Chlorophenyl phenyl ether 4-Nitroaniline 4-Nitroaniline 4-Nitrophenol	Hg/L Hg/L Hg/L Hg/L Hg/L Hg/L Hg/L Hg/L																
Acenaphthene Acenaphthylene Acetophenone Anthracene Atrazine Benzaldehyde Benzo(a)anthracene Benzo(a)pyrene Benzo(b)fluoranthene	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	-	- - - - - -	- - - - - - -	- - - - - - -	- - - - - -	 	 	- - - - - - -	- - - - - - - - -	- - - - - - - - -	- - - - - - -	 	- - - - - - - - -	 	 	
Benzo(g,h,i)perylene Benzo(k)fluoranthene Biphenyl (1,1-Biphenyl) bis(2-Chloroethoxy)methane bis(2-Chloroethyl)ether bis(2-Ethylhexyl)phthalate (DEHP) Butyl benzylphthalate (BBP) Caprolactam Carbazole	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	-	- - - - - -	-	- - - - - -	- - - - - -	- - - - - - - -	- - - - - - -	-	 	 	- - - - - -	 	- - - - - - - - -	 	-	
Chrysene Dibenz(a,h)anthracene Dibenzofuran Diethyl phthalate Dimethyl phthalate Di-n-butylphthalate (DBP) Di-n-octyl phthalate (DnOP) Fluoranthene Fluorene	µg/L µg/L µg/L µg/L µg/L µg/L µg/L µg/L	- - - - - - -	- - - - - - -	 	 	 	 	 	 	 	 	- - - - - - -	 	 	 	 	
Hexachlorobenzene	μg/L		-		-												-

Table 3.1

Sample Location		9-4	CH-20	CH-42	CH-42A	CH-43	CH-44	MW-X033Y147S	MW-X043Y176	MW-X047Y236	MW-X085Y070S-1	MW-X085Y070S-2	MW-X146Y084	MW-X146Y084	MW-X169Y058S-1	MW-X227Y054	MW-X242Y060S
Sample Date	Unite	05/24/2023	05/24/2023	05/22/2023	05/22/2023	05/22/2023	05/22/2023	05/25/2023	05/23/2023	05/23/2023	05/25/2023	05/25/2023	05/24/2023	05/24/2023	05/25/2023	05/23/2023	05/24/2023
Parameters	Units																
Hexachlorobutadiene	μg/L																
Hexachlorocyclopentadiene	μg/L																
Hexachloroethane	μg/L																
Indeno(1,2,3-cd)pyrene	μg/L																
Isophorone	μg/L																
Naphthalene	μg/L																
Nitrobenzene	μg/L																
N-Nitrosodi-n-propylamine	μg/L																
N-Nitrosodiphenylamine	μg/L																
Pentachlorophenol	μg/L																
Phenanthrene	μg/L																
Phenol	μg/L																
Pyrene	μg/L																-
Volatile Organic Compounds (VOCs)																	
1,1,1-Trichloroethane	ua/l	1.0 U	1.0 U						-								
1,1,2,2-Tetrachloroethane	ug/L ug/L	1.0 U	1.0 U					 			 		-				
1,1,2-Trichloroethane	ug/L	1.0 U	1.0 U					 			 						
1,1-Dichloroethane	ug/L	1.0 U	1.0 U					 									
1,1-Dichloroethene	ug/L	1.0 U	1.0 U														
1,2,4-Trichlorobenzene	ug/L																
1,2-Dibromo-3-chloropropane (DBCP)	ug/L																
1,2-Dibromoethane (Ethylene dibromide)	ug/L																
1,2-Dichlorobenzene	ug/L	1.0 U	1.0 U														
1,2-Dichloroethane	ug/L	1.0 U	1.0 U														
1,2-Dichloropropane	ug/L	1.0 U	1.0 U														
1,3-Dichlorobenzene	ug/L	1.0 U	1.0 U														
1,4-Dichlorobenzene	ug/L	1.0 U	1.0 U														
2-Butanone (Methyl ethyl ketone) (MEK)	ug/L																
2-Chloroethyl vinyl ether	ug/L	10 U	10 U														
2-Hexanone	ug/L																
4-Methyl-2-pentanone (Methyl isobutyl ketone) (MIBK)	ug/L																
Acetone	ug/L																
Benzene	ug/L	1.0 U	1.0 U														
Bromodichloromethane	ug/L	1.0 U	1.0 U														
Bromoform	ug/L	1.0 U	1.0 U														
Bromomethane (Methyl bromide)	ug/L	1.0 U	1.0 U														
Carbon disulfide	ug/L																
Carbon tetrachloride	ug/L	1.0 U	1.0 U														
Chlorobenzene	ug/L	1.0 U	1.0 U														
Chloroethane	ug/L	1.0 U	1.0 U														
Chloroform (Trichloromethane)	ug/L	1.0 U	1.0 U														
Chloromethane (Methyl chloride)	ug/L	1.0 U	1.0 U														
cis-1,2-Dichloroethene	ug/L													-			-
cis-1,3-Dichloropropene	ug/L	1.0 U	1.0 U												-		
Cyclohexane	ug/L																
Dibromochloromethane	ug/L	1.0 U	1.0 U														
Dichlorodifluoromethane (CFC-12)	ug/L	1.0 U	1.0 U														
Ethylbenzene	ug/L	1.0 U	1.0 U														
Isopropyl benzene	ug/L																
Methyl acetate	ug/L																
Methyl cyclohexane	ug/L																
Methyl tert butyl ether (MTBE)	ug/L																
Methylene chloride	ug/L	5.0 U	5.0 U														
Styrene	ug/L																
Tetrachloroethene	ug/L	1.0 U	1.0 U														
Toluene	ug/L	1.0 U	1.0 U														
trans-1,2-Dichloroethene	ug/L	1.0 U	1.0 U														
trans-1,3-Dichloropropene	ug/L	1.0 U	1.0 U														
Trichloroethene	ug/L																
Trichlorofluoromethane (CFC-11)	ug/L	1.0 U	1.0 U														
Trifluorotrichloroethane (CFC-113)	ug/L																
Vinyl chloride	ug/L	1.0 U	1.0 U										1.0 U	1.0 U	0.70 J		
Xylenes (total)	ug/L																

Sample Location Sample Date Parameters	Units	9-4 05/24/2023	CH-20 05/24/2023	CH-42 05/22/2023	CH-42A 05/22/2023	CH-43 05/22/2023	CH-44 05/22/2023	MW-X033Y147S 05/25/2023	MW-X043Y176 05/23/2023	MW-X047Y236 05/23/2023	MW-X085Y070S-1 05/25/2023	MW-X085Y070S-2 05/25/2023	MW-X146Y084 05/24/2023	MW-X146Y084 05/24/2023	MW-X169Y058S-1 05/25/2023	MW-X227Y054 05/23/2023	MW-X242Y060S 05/24/2023
General Chemistry																	
Chloride	ug/L								-				1900000	2000000			-
Field Parameters																	
Conductivity, field	uS/cm	592	757	0.564	0.483	0.815	0.841	1641	1.542	0.692	8.715	4.665	5124	5124	1.862	1796	1.702
Dissolved oxygen (DO), field	ug/L	2570	190	11100	5190	440	400	4460	180	1620	6280	9370	290	290	7350	580	1190
Flow rate	mL/min					500	500									125	
Oxidation reduction potential (ORP), field	millivolts	-83.4	-203.9	32.3	-36.9	-0.9	94.1	4.2	-101.8	18.3	-163.0	-156.0	-152.0	-152.0	-31.9	-106.3	-300.9
pH, field	s.u.	7.10	7.80	6.08	6.91	6.89	6.77	6.77	6.89	7.08	6.99	7.33	7.33	7.33	7.65	7.15	7.12
Temperature, sample	Deg C	16.05	14.59	17.59	15.85	17.48	15.97	17.65	14.06	16.97	18.25	18.64	23.06	23.06	14.84	18.11	15.91
Turbidity, field	NTU	3.69	6.15	3.16	2.46	9.67	1.58	10.77	17.1	2.36	4.36	8.42	21.6	21.6	5.31	34.7	2.98
Volume purged	gal	0	0		0	6.66	5.84	0	0	0	0	0	0	0	0	2.11	-

Sample Location Sample Date Parameters	Units	MW-X261Y356D-3 05/23/2023	MW-X277Y100 05/24/2023	MW-X297Y305D-2 05/23/2023	MW-X300Y199I-1 05/23/2023	MW-X300Y199I-2 05/23/2023	MW-X315Y115 05/23/2023	MW-X315Y150 05/23/2023	MW-X315Y150 05/23/2023	ST-59 05/25/2023	ST-59 05/25/2023	Tributary 3-3 05/25/2023
Polychlorinated biphenyl (PCBs)												
Aroclor-1016 (PCB-1016) Aroclor-1221 (PCB-1221) Aroclor-1232 (PCB-1232) Aroclor-1242 (PCB-1242) Aroclor-1248 (PCB-1248) Aroclor-1254 (PCB-1254) Aroclor-1260 (PCB-1260) Total PCBs	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.091 J 0.095 U 0.095 U 0.095 U 0.091 J	0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.099 U 0.099 U 0.099 U 0.24 0.099 U 0.099 U 0.099 U 0.24	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U	0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U ND	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U
Aroclor-1016 (PCB-1016) (dissolved) Aroclor-1221 (PCB-1221) (dissolved) Aroclor-1232 (PCB-1232) (dissolved) Aroclor-1242 (PCB-1242) (dissolved) Aroclor-1248 (PCB-1248) (dissolved) Aroclor-1254 (PCB-1254) (dissolved) Aroclor-1260 (PCB-1260) (dissolved) Total PCBs (dissolved)	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U ND
Semi-Volatile Organic Compounds (SVOCs)												
2,2'-Oxybis(1-chloropropane) (bis(2-Chloroisopropyl) ether) 2,4,5-Trichlorophenol 2,4-Dichlorophenol 2,4-Dimethylphenol	μg/L μg/L μg/L μg/L μg/L	 	9.5 U 9.5 U 9.5 U 9.5 U 9.5 U	 	 	 	 	 	 	 	 	
2,4-Dinitrophenol 2,4-Dinitrotoluene 2,6-Dinitrotoluene 2-Chloronaphthalene 2-Chlorophenol	µg/L µg/L µg/L µg/L µg/L	 	48 U 9.5 U 9.5 U 9.5 U 9.5 U	 	 	 	 	 	 	 	 	
2-Methylnaphthalene 2-Methylphenol 2-Nitroaniline 2-Nitrophenol 3&4-Methylphenol	μg/L μg/L μg/L μg/L μg/L	 	9.5 U 9.5 U 48 U 9.5 U 9.5 U	 	 	 	 	 	- - - -	 	 	
3,3'-Dichlorobenzidine 3-Nitroaniline 4,6-Dinitro-2-methylphenol 4-Bromophenyl phenyl ether 4-Chloro-3-methylphenol 4-Chloroaniline	µg/L µg/L µg/L µg/L µg/L µg/L	 	48 U 48 U 48 U 9.5 U 9.5 U 9.5 U	 	 	 	- - - -	 	 	- - - -	- - - -	
4-Chlorophenyl phenyl ether 4-Nitroaniline 4-Nitrophenol Acenaphthene Acenaphthylene	µg/L µg/L µg/L µg/L µg/L	 	9.5 U 48 U 48 U 9.5 U 9.5 U	 	 	 	 	 	 	 	 	
Acetophenone Anthracene Atrazine Benzaldehyde Benzo(a)anthracene	µg/L µg/L µg/L µg/L µg/L	 	9.5 U 9.5 U 9.5 U 9.5 U 9.5 U	 	 	 	 	 	 	 	 	
Benzo(a)pyrene Benzo(b)fluoranthene Benzo(g,h,i)perylene Benzo(k)fluoranthene Biphenyl (1,1-Biphenyl) bis(2-Chloroethoxy)methane	µg/L µg/L µg/L µg/L µg/L µg/L	 	9.5 U 9.5 U 9.5 U 9.5 U 9.5 U 9.5 U	 	 	 	- - - -	 	- - - -	- - - -	- - - - -	
bis(2-Chiloroethyl)ether bis(2-Ethylhexyl)phthalate (DEHP) Butyl benzylphthalate (BBP) Caprolactam Carbazole	μg/L μg/L μg/L μg/L μg/L μg/L	 	9.5 U 9.5 U 9.5 U R 9.5 U		 	- - - -	- - - -	- - - -	= = = = = = = = = = = = = = = = = = = =	- - - -	 	- - - -
Chrysene Dibenz(a,h)anthracene Dibenzofuran Diethyl phthalate Dimethyl phthalate	µg/L µg/L µg/L µg/L µg/L	 	9.5 U 9.5 U 9.5 U 9.5 U 9.5 U	- - - -	 	 	 	 	- - - -	 	 	
Di-n-butylphthalate (DBP) Di-n-octyl phthalate (DnOP) Fluoranthene Fluorene Hexachlorobenzene	μg/L μg/L μg/L μg/L μg/L	 	9.5 U 9.5 U 9.5 U 9.5 U 9.5 U	 		 	- - - -	 	- - - -	- - - -	 	

Sample Location Sample Date		MW-X261Y356D-3 05/23/2023	MW-X277Y100 05/24/2023	MW-X297Y305D-2 05/23/2023	MW-X300Y199I-1 05/23/2023	MW-X300Y199I-2 05/23/2023	MW-X315Y115 05/23/2023	MW-X315Y150 05/23/2023	MW-X315Y150 05/23/2023	ST-59 05/25/2023	ST-59 05/25/2023	Tributary 3-3 05/25/2023
Parameters	Units											
Hexachlorobutadiene	μg/L		9.5 U									
Hexachlorocyclopentadiene	μg/L		48 U									
Hexachloroethane	μg/L		9.5 U									
Indeno(1,2,3-cd)pyrene	μg/L		9.5 U									
Isophorone	μg/L		9.5 U									
Naphthalene	μg/L		9.5 U									
Nitrobenzene	μg/L		9.5 U									
N-Nitrosodi-n-propylamine	μg/L		9.5 U									
N-Nitrosodiphenylamine	μg/L		9.5 U									
Pentachlorophenol	μg/L		9.5 U					-				
Phenanthrene	μg/L		9.5 U									
Phenol	μg/L		9.5 U									
Pyrene	μg/L		9.5 U					-				
Volatile Organic Compounds (VOCs)												
1,1,1-Trichloroethane	ug/L		1.0 U									
1,1,2,2-Tetrachloroethane	ug/L		1.0 U					-				
1,1,2-Trichloroethane	ug/L		1.0 U									
1,1-Dichloroethane	ug/L		1.0 U									
1,1-Dichloroethene	ug/L		1.0 U									
1,2,4-Trichlorobenzene	ug/L		1.0 U									
1,2-Dibromo-3-chloropropane (DBCP)	ug/L		2.0 U									
1,2-Dibromoethane (Ethylene dibromide)	ug/L		1.0 U									
1,2-Dichlorobenzene 1,2-Dichloroethane	ug/L		1.0 U 1.0 U									
1,2-Dichlorographie 1,2-Dichloropropane	ug/L		1.0 U									
1,3-Dichloropane	ug/L ug/L		1.0 U									
1,4-Dichlorobenzene	ug/L		1.0 U									
2-Butanone (Methyl ethyl ketone) (MEK)	ug/L		10 U									
2-Chloroethyl vinyl ether	ug/L											
2-Hexanone	ug/L		10 U									
4-Methyl-2-pentanone (Methyl isobutyl ketone) (MIBK)	ug/L		10 U									
Acetone	ug/L		10 U									
Benzene	ug/L		1.0 U									
Bromodichloromethane	ug/L		1.0 U									
Bromoform	ug/L		1.0 U									
Bromomethane (Methyl bromide)	ug/L		1.0 U									
Carbon disulfide	ug/L		1.0 U									
Carbon tetrachloride	ug/L		1.0 U									
Chlorobenzene	ug/L		1.0 U								-	
Chloroethane	ug/L		1.0 U									
Chloroform (Trichloromethane)	ug/L		1.0 U 1.0 U									
Chloromethane (Methyl chloride) cis-1,2-Dichloroethene	ug/L ug/L		1.0 U									
cis-1,3-Dichloropropene	ug/L		1.0 U	-			-			-	-	-
Cyclohexane	ug/L ug/L		1.0 U			-	- 	-				
Dibromochloromethane	ug/L		1.0 U									
Dichlorodifluoromethane (CFC-12)	ug/L		1.0 U									
Ethylbenzene	ug/L		1.0 U									
Isopropyl benzene	ug/L		1.0 U									
Methyl acetate	ug/L		10 U									
Methyl cyclohexane	ug/L		1.0 U									
Methyl tert butyl ether (MTBE)	ug/L		1.0 U									
Methylene chloride	ug/L		5.0 U					-				
Styrene	ug/L		1.0 U									
Tetrachloroethene	ug/L		1.0 U									
Toluene	ug/L		1.0 U									
trans-1,2-Dichloroethene	ug/L		1.0 U									
trans-1,3-Dichloropropene	ug/L		1.0 U									
Trichloroethene	ug/L		1.0 U									
Trichlorofluoromethane (CFC-11) Trifluorotrichloroethane (CFC-113)	ug/L		1.0 U 1.0 U	 					 			
Vinyl chloride	ug/L		1.0 U		 							
Xylenes (total)	ug/L ug/L		2.0 U									
7.550 (total)	ug/L	-	2.0 0			-	-	-	-	-	-	

Page 6 of 6

Summary of Analytical Results - El CA750 First Half 2023 Sampling Event East Plant TSCA Vault Annual Report - Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Sample Location Sample Date Parameters	Units	MW-X261Y356D-3 05/23/2023	MW-X277Y100 05/24/2023	MW-X297Y305D-2 05/23/2023	MW-X300Y199I-1 05/23/2023	MW-X300Y199I-2 05/23/2023	MW-X315Y115 05/23/2023	MW-X315Y150 05/23/2023	MW-X315Y150 05/23/2023	ST-59 05/25/2023	ST-59 05/25/2023	Tributary 3-3 05/25/2023
General Chemistry												
Chloride	ug/L							-		18000	18000	
Field Parameters												
Conductivity, field	uS/cm	0.501	0.932	0.366	0.287	0.314	0.429	0.415	0.415	519	519	0.759
Dissolved oxygen (DO), field	ug/L	1020	1460	2170	1570	1020	1200	1900	1900	42100	42100	14600
Flow rate	mL/min											
Oxidation reduction potential (ORP), field	millivolts	-168.5	-34.9	-78.4	-99.8	-111.9	-24.8	-79.9	-79.9	-22.3	-22.3	255.6
pH, field	s.u.	7.02	7.09	7.23	7.23	7.68	7.72	7.47	7.47	3.05	3.05	2.57
Temperature, sample	Deg C	16.54	14.75	14.23	15.68	16.16	16.03	17.24	17.24	13.82	13.82	22.06
Turbidity, field	NTU	3.08	3.84	3.14	3.01	2.97	23.2	15.4	15.4	2.44	2.44	7.82
Volume purged	gal	0		0	0		0	0	0	0	0	0

Notes:
U - Not detected at the associated reporting limit.
J - Estimated concentration.
R - Rejected.
ND - Non Detect.

Table 3.2

Sample Location Sample Date Parameters	Units	9-4 11/15/2023	CH-20 11/15/2023	CH-42 11/13/2023	CH-42A 11/13/2023	CH-43 11/13/2023	CH-44 11/13/2023	MW-X033Y147S 11/15/2023	MW-X043Y176 11/16/2023	MW-X047Y236 11/16/2023	MW-X085Y070S-1 11/15/2023	MW-X085Y070S-2 11/15/2023	MW-X146Y084 11/15/2023	MW-X146Y084 11/15/2023	MW-X169Y058S-1 11/15/2023
Polychlorinated biphenyl (PCBs)															
Aroclor-1016 (PCB-1016) Aroclor-1221 (PCB-1221) Aroclor-1232 (PCB-1232) Aroclor-1242 (PCB-1242) Aroclor-1248 (PCB-1248) Aroclor-1254 (PCB-1254) Aroclor-1260 (PCB-1260) Total PCBs	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	0.11 U 0.11 U 0.11 U 0.34 0.11 U 0.11 U 0.11 U 0.34	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U ND	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U	0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U	0.14 U 0.14 U 0.14 U 0.14 U 0.14 U 0.14 U 0.14 U 0.14 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U ND	0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U 0.097 U ND	0.10 U 0.10 U 0.10 U 0.078 J 0.10 U 0.10 U 0.10 U 0.078 J	0.21 U 0.21 U 0.21 U 4.1 0.21 U 0.21 U 0.21 U 4.1	0.40 U 0.40 U 0.40 U 4.2 0.40 U 0.40 U 0.40 U	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U
Aroclor-1016 (PCB-1016) (dissolved) Aroclor-1221 (PCB-1221) (dissolved) Aroclor-1232 (PCB-1232) (dissolved) Aroclor-1242 (PCB-1242) (dissolved) Aroclor-1248 (PCB-1248) (dissolved) Aroclor-1254 (PCB-1254) (dissolved) Aroclor-1260 (PCB-1260) (dissolved) Total PCBs (dissolved)	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U 0.10 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.098 U 0.098 U 0.098 U 0.098 U 0.098 U 0.098 U 0.098 U ND	 	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND	0.098 U 0.098 U 0.098 U 0.098 U 0.098 U 0.098 U ND	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U ND	0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U 0.11 U	0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U 0.096 U ND	0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U 0.095 U ND
Semi-Volatile Organic Compounds (SVOCs)															
2,2'-Oxybis(1-chloropropane) (bis(2-Chloroisopropyl) ether) 2,4,5-Trichlorophenol 2,4,6-Trichlorophenol 2,4-Dichlorophenol 2,4-Dinitrobluene 2,4-Dinitrotoluene 2,6-Dinitrotoluene 2,6-Dinitrotoluene 2-Chloronaphthalene 2-Chlorophenol 2-Methylphenol 2-Methylphenol 2-Nitroaniline 2-Nitroaniline 3-Nitroaniline 3-Nitroaniline 4,6-Dinitro-2-methylphenol 4-Bromophenyl phenyl ether 4-Chloro-3-methylphenol 4-Chloroaniline 4-Chlorophenyl phenyl ether 4-Nitroaniline 4-Nitroaniline 4-Nitroaniline 4-Nitroaniline 4-Nitroaniline 4-Nitrophenol Acenaphthene Acenaphthylene	µg/L µg/L								 						
Acetophenone Anthracene Atrazine Benzaldehyde Benzo(a)anthracene Benzo(a)pyrene Benzo(b)fluoranthene Benzo(g,h,i)perylene	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	 	- - - - - -	 	 	 	- - - - - - -	- - - - - -	- - - - - -	 	 	 	- - - - - -	- - - - - -	- - - - - - -
Benzo(k)fluoranthene Biphenyl (1,1-Biphenyl) bis(2-Chloroethoxy)methane bis(2-Chloroethyl)ether bis(2-Ethylhexyl)phthalate (DEHP) Butyl benzylphthalate (BBP) Caprolactam Carbazole	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	 	 	 	 	 	 	 	 	 	 	 	 	- - - - - -	
Chrysene Dibenz(a,h)anthracene Dibenzofuran Diethyl phthalate Dimethyl phthalate Di-n-butylphthalate (DBP) Di-n-octyl phthalate (DnOP)	µg/L µg/L µg/L µg/L µg/L µg/L µg/L	 	 	 	 	 	- - - - -	 	 	 	 	 	 	- - - - - -	- - - - - -

Table 3.2

Sample Location		9-4	CH-20	CH-42	CH-42A	CH-43	CH-44	MW-X033Y147S	MW-X043Y176	MW-X047Y236	MW-X085Y070S-1	MW-X085Y070S-2	MW-X146Y084	MW-X146Y084	MW-X169Y058S-1
Sample Date		11/15/2023	11/15/2023	11/13/2023	11/13/2023	11/13/2023	11/13/2023	11/15/2023	11/16/2023	11/16/2023	11/15/2023	11/15/2023	11/15/2023	11/15/2023	11/15/2023
Parameters	Units														
Fluoranthene	μg/L														
Fluorene	μg/L														
Hexachlorobenzene	μg/L														
Hexachlorobutadiene	μg/L														
Hexachlorocyclopentadiene	μg/L														
Hexachloroethane	μg/L														
Indeno(1,2,3-cd)pyrene	μg/L														
Isophorone	μg/L														
Naphthalene	μg/L														
Nitrobenzene	μg/L											-		-	-
N-Nitrosodi-n-propylamine	μg/L														
N-Nitrosodiphenylamine	μg/L					 									
Pentachlorophenol Phenanthrene	μg/L			<u></u>	 	 	 					 	 		
Phenol	μg/L μg/L	 		 	 		 	 	 		 	 	 	 	
Pyrene	μg/L														
, ·-	ra-														
Volatile Organic Compounds (VOCs)															
1,1,1-Trichloroethane	μg/L	1.0 U	1.0 U												
1,1,2,2-Tetrachloroethane	μg/L	1.0 U	1.0 U												
1,1,2-Trichloroethane	μg/L	1.0 U	1.0 U												
1,1-Dichloroethane	μg/L	1.0 U	1.0 U												
1,1-Dichloroethene	μg/L	1.0 U	1.0 U												
1,2,4-Trichlorobenzene	μg/L														
1,2-Dibromo-3-chloropropane (DBCP)	μg/L														
1,2-Dibromoethane (Ethylene dibromide)	μg/L													-	
1,2-Dichlorobenzene	μg/L	1.0 U	1.0 U												
1,2-Dichloroethane	μg/L	1.0 U	1.0 U												
1,2-Dichloropropane	μg/L	1.0 U	1.0 U									-		-	
1,3-Dichlorobenzene	μg/L	1.0 U	1.0 U												
1,4-Dichlorobenzene	μg/L	1.0 U	1.0 U												
2-Butanone (Methyl ethyl ketone) (MEK) 2-Chloroethyl vinyl ether	μg/L	 10 U	 10 U												-
2-Hexanone	μg/L μg/L		10 0			 									
4-Methyl-2-pentanone (Methyl isobutyl ketone) (MIBK)	μg/L														
Acetone	μg/L					<u></u>									
Benzene	μg/L	1.0 U	1.0 U												
Bromodichloromethane	μg/L	1.0 U	1.0 U												
Bromoform	μg/L	1.0 U	1.0 U												
Bromomethane (Methyl bromide)	μg/L	1.0 U	1.0 U												
Carbon disulfide	μg/L														
Carbon tetrachloride	μg/L	1.0 U	1.0 U												
Chlorobenzene	μg/L	1.0 U	1.0 U												
Chloroethane	μg/L	1.0 U	1.0 U											-	
Chloroform (Trichloromethane)	μg/L "	1.0 U	1.0 U												
Chloromethane (Methyl chloride)	μg/L	1.0 U	1.0 U					-							-
cis-1,2-Dichloroethene	μg/L	1011	4.011					-							-
cis-1,3-Dichloropropene Cyclohexane	μg/L ug/l	1.0 U	1.0 U			 									
Dibromochloromethane	μg/L μg/L	 1.0 U	 1.0 U				 								
Dichlorodifluoromethane (CFC-12)	μg/L	1.0 UJ	1.0 UJ		 	 		 			 	 	 	 	-
Ethylbenzene	μg/L	1.0 U	1.0 U												
Isopropyl benzene	μg/L														
Methyl acetate	μg/L														
Methyl cyclohexane	μg/L														
Methyl tert butyl ether (MTBE)	μg/L														
Methylene chloride	μg/L	5.0 U	5.0 U												
Styrene	μg/L														
Tetrachloroethene	μg/L	1.0 U	1.0 U												
Toluene	μg/L	1.0 U	1.0 U												-
trans-1,2-Dichloroethene	μg/L	1.0 U	1.0 U												
trans-1,3-Dichloropropene	μg/L "	1.0 U	1.0 U												
Trichloroethene	μg/L														
Trichlorofluoromethane (CFC-11)	μg/L	1.0 U	1.0 U	-				-				-			
Trifluorotrichloroethane (CFC-113)	μg/L	 1 0 I I	1011										 1.0 U	 1.0 U	0.05.1
Vinyl chloride Xylenes (total)	μg/L μg/L	1.0 U 	1.0 U 		 	 			 				1.0 0	1.0 0	0.95 J
7.570100 (total)	µg/∟	==	==	==	==			==	==		==				

Sample Location Sample Date Parameters	Units	9-4 11/15/2023	CH-20 11/15/2023	CH-42 11/13/2023	CH-42A 11/13/2023	CH-43 11/13/2023	CH-44 11/13/2023	MW-X033Y147S 11/15/2023	MW-X043Y176 11/16/2023	MW-X047Y236 11/16/2023	MW-X085Y070S-1 11/15/2023	MW-X085Y070S-2 11/15/2023	MW-X146Y084 11/15/2023	MW-X146Y084 11/15/2023	MW-X169Y058S-1 11/15/2023
General Chemistry															
Chloride	μg/L		-									-	1900000	1800000	
Field Parameters															
Conductivity, field	uS/cm	0.582	0.667	0.652	0.565	0.906	1.028	1577	1585	610	7.920	4.442	4544	4544	1.811
Dissolved oxygen (DO), field	μg/L	250	310	11930	2710	2470	6300	1120	1560	2090	7020	10650	910	910	29000
Flow rate	mL/min	500	500			500	500	500	500	500			500	500	
Oxidation reduction potential (ORP), field	millivolts	-141.1	-190.3	-87.9	25.5	4.0	76.0	29.2	-25.5	-53.0	-138.9	-180.9	-96.6	-96.6	-52.4
pH, field	s.u.	7.40	7.55	8.32	8.04	7.41	7.21	6.87	6.96	7.40	6.97	7.52	7.58	7.58	7.55
Temperature, sample	Deg C	15.59	14.52	13.87	14.71	14.26	16	16.74	13.73	13.92	18.19	19.06	17.49	17.49	15.25
Turbidity, field	NTU	2.82	7.09	25.9	15.9	14.9	3.15	23.6	2.89	0.95	35.3	79.1	66.6	66.6	15.9
Volume purged	gal	2.81	5.15	ND	ND	3.89		4	4.16	4.77	ND	ND	8.65	8.65	ND

Notes: U - Not detected at the associated reporting limit.

J - Estimated concentration.

UJ - Not detected; associated reporting limit is estimated.

Table 3.2

Arcolor-1221 (PCB-1221)	sample Location sample Date darameters Ui	4 MW-X242Y060S MW-X261Y356D-3 MW-X277Y10 11/14/2023 11/14/2023 11/16/2023		MW-X315Y115 MW-X315Y150 MW-X315Y150 ST-59 Tributary 3-3 11/14/2023 11/14/2023 11/16/2023 11/16/2023
Ancolor-1221 (PCB-1221)	olychlorinated biphenyl (PCBs)			
Aroclor-1221 (PCB-1221) (dissolved) µg/L 0.095 U 0.95 U 0.48 U 0.11 U 0.095 U 0.11 U 0.	ντοclor-1221 (PCB-1221) μ ντοclor-1232 (PCB-1232) μ ντοclor-1242 (PCB-1242) μ ντοclor-1248 (PCB-1248) μ ντοclor-1254 (PCB-1254) μ ντοclor-1260 (PCB-1260) μ	19 U 0.10 U 0.095 U 19 U 0.10 U 0.095 U 450 0.10 U 0.34 19 U 0.10 U 0.095 U 19 U 0.10 U 0.095 U 19 U 0.10 U 0.095 U	0.095 U 0.098 U 0.10 U 0.095 U 0.098 U 0.10 U 0.095 U 0.15 0.10 U 0.095 U 0.098 U 0.10 U 0.095 U 0.098 U 0.10 U 0.095 U 0.098 U 0.10 U	0.10 U 0.095 U 0.10 U 0.095 U 0.097 U 0.10 U 0.095 U 0.10 U 0.095 U 0.097 U 0.098 J 0.073 J 0.084 J 0.095 U 0.097 U 0.10 U 0.095 U 0.10 U 0.095 U 0.097 U 0.10 U 0.095 U 0.10 U 0.095 U 0.097 U 0.10 U 0.095 U 0.10 U 0.095 U 0.097 U 0.10 U 0.095 U 0.10 U 0.095 U 0.097 U
Semi-Volatile Organic Compounds (SVOCs)	μroclor-1221 (PCB-1221) (dissolved) μroclor-1232 (PCB-1232) (dissolved) μroclor-1232 (PCB-1232) (dissolved) μroclor-1242 (PCB-1242) (dissolved) μroclor-1248 (PCB-1248) (dissolved) μroclor-1254 (PCB-1254) (dissolved) μroclor-1260 (PCB-1260) (dissolved) μroclor-1260 (PCB-1260) (dissolved) μroclor-1260 (PCB-1260) μroclor-1260 (PCB-1260) μroclor-1260 (PCB-1260)	0.48 U 0.11 U 0.10 U 0.48 U 0.11 U 0.10 U 3.5 0.11 U 0.10 U 0.48 U 0.11 U 0.10 U 0.48 U 0.11 U 0.10 U 0.48 U 0.11 U 0.10 U	0.095 U 0.095 U 0.11 U 0.095 U 0.095 U 0.11 U	0.095 U 0.13 U 0.11 U 0.10 U 0.097 U 0.095 U 0.13 U 0.11 U 0.10 U 0.097 U 0.095 U 0.13 U 0.11 U 0.10 U 0.097 U 0.095 U 0.13 U 0.11 U 0.10 U 0.097 U 0.095 U 0.13 U 0.11 U 0.10 U 0.097 U 0.095 U 0.13 U 0.11 U 0.10 U 0.097 U 0.095 U 0.13 U 0.11 U 0.10 U 0.097 U
2,2'-Oxybis(1-chloropropane) (bis(2-Chloroisopropyl) ether) µg/L 10 U	,2'-Oxybis(1-chloropropane) (bis(2-Chloroisopropyl) ether) μ			
2,4,5-Trichlorophenol µg/L 10 U	,4,6-Trichlorophenol μ,4-Dichlorophenol μ	10 U 10 U		
2,4-Dinitrophenol	.4-Dinitrophenol μ4-Dinitrotoluene μ6-Dinitrotoluene μ	52 U 10 U 10 U		
2-Chloronaphthalene	-Chlorophenol μ -Methylnaphthalene μ	10 U 10 U	 	
2-Nitrophenol $\mu g/L$ 52 U	-Nitroaniline μ -Nitrophenol μ	52 U 10 U		
3,3'-Dichlorobenzidine µg/L 52 U	-Nitroaniline μ, ,6-Dinitro-2-methylphenol μ	52 U 52 U	 	
4-Bromophenyl ether µg/L 10 U	-Chloro-3-methylphenol μ -Chloroaniline μ	10 U 10 U	 	
4-Nitroaniline 4	-Nitroaniline μ -Nitrophenol μ ιcenaphthene μ	52 U 52 U 10 U		
Aceraphthylene	cetophenone μ unthracene μ	10 U 10 U	 	
Atrazine	μ denzaldehyde μ denzo(a)anthracene μ	10 U 10 U	 	
Benzo(b)fluoranthene	$ ext{lenzo(b)}$ fluoranthene μ Benzo(g,h,i)perylene μ	10 U 10 U 10 U		
Biphenyl (1,1-Biphenyl)	is(2-Chloroethoxy)methane μ is(2-Chloroethyl)ether μ	10 U 10 U	 	
bis(2-Ethylhexyl)phthalate (DEHP)	kutyl benzylphthalate (BBP) μ Caprolactam μ	10 U 10 U		
Chrysene	Chrysene μ Dibenz(a,h)anthracene μ Dibenzofuran μ	10 U 10 U 10 U		
Diethyl phthalate µg/L 10 U <t< th=""><th>imethyl phthalate μ bi-n-butylphthalate (DBP) μ</th><th> 10 U 10 U</th><th></th><th></th></t<>	imethyl phthalate μ bi-n-butylphthalate (DBP) μ	10 U 10 U		

Table 3.2

Sample Location Sample Date		MW-X169Y058S-1 11/15/2023	MW-X227Y054 11/14/2023	MW-X242Y060S 11/14/2023	MW-X261Y356D-3 11/14/2023	MW-X277Y100 11/16/2023	MW-X297Y305D-2 11/14/2023	MW-X300Y199I-1 11/14/2023	MW-X300Y199I-2 11/14/2023	MW-X315Y115 11/14/2023	MW-X315Y150 11/14/2023	MW-X315Y150 11/14/2023	ST-59 11/16/2023	Tributary 3-3 11/16/2023
Parameters	Units													
Fluoranthene	μg/L					10 U								
Fluorene	μg/L					10 U								
Hexachlorobenzene	μg/L					10 U								
Hexachlorobutadiene	μg/L					10 U								
Hexachlorocyclopentadiene	μg/L					52 U								
Hexachloroethane Indeno(1,2,3-cd)pyrene	μg/L					10 U 10 U								
Isophorone	μg/L μg/L					10 U	 	 			 	 	 	
Naphthalene	μg/L					10 U								
Nitrobenzene	μg/L					10 U								
N-Nitrosodi-n-propylamine	μg/L					10 U								
N-Nitrosodiphenylamine	μg/L					10 U								
Pentachlorophenol Phenanthrene	μg/L					10 U 10 U								
Phenol	μg/L μg/L	 	 		 	0.74 J		 		 				-
Pyrene	μg/L					10 U								
Volatile Organic Compounds (VOCs)														
1,1,1-Trichloroethane	μg/L					1.0 U								
1,1,2,2-Tetrachloroethane	μg/L μg/L	 				1.0 U								
1,1,2-Trichloroethane	μg/L					1.0 U								
1,1-Dichloroethane	μg/L					1.0 U								
1,1-Dichloroethene	μg/L					1.0 U								
1,2,4-Trichlorobenzene	μg/L					1.0 U								
1,2-Dibromo-3-chloropropane (DBCP) 1,2-Dibromoethane (Ethylene dibromide)	μg/L μg/L					2.0 U 1.0 U								
1,2-Dichlorobenzene	μg/L					1.0 U								
1,2-Dichloroethane	μg/L					1.0 U								
1,2-Dichloropropane	μg/L					1.0 U								
1,3-Dichlorobenzene	μg/L					1.0 U								
1,4-Dichlorobenzene 2-Butanone (Methyl ethyl ketone) (MEK)	μg/L μg/L	 				1.0 U 10 U		 						
2-Chloroethyl vinyl ether	μg/L μg/L	 						 			 			-
2-Hexanone	μg/L					10 U								
4-Methyl-2-pentanone (Methyl isobutyl ketone) (MIBK)	μg/L					10 U								
Acetone	μg/L					10 U								
Benzene	μg/L					1.0 U								
Bromodichloromethane Bromoform	μg/L μg/L	 				1.0 U 1.0 U		 			 			
Bromomethane (Methyl bromide)	μg/L					1.0 U								
Carbon disulfide	μg/L					1.0 U								
Carbon tetrachloride	μg/L					1.0 U								
Chlorobenzene	μg/L					1.0 U								
Chloroftom (Triphloromothono)	μg/L					1.0 U								
Chloroform (Trichloromethane) Chloromethane (Methyl chloride)	μg/L μg/L					1.0 U 1.0 U		 						
cis-1,2-Dichloroethene	μg/L					1.0 U								
cis-1,3-Dichloropropene	μg/L					1.0 U								
Cyclohexane	μg/L					1.0 U								
Dibromochloromethane	μg/L					1.0 U	-							
Dichlorodifluoromethane (CFC-12) Ethylbenzene	μg/L μg/L		 			1.0 U 1.0 U		 			 			
Isopropyl benzene	μg/L					1.0 U								
Methyl acetate	μg/L					10 U								
Methyl cyclohexane	μg/L					1.0 U								
Methyl tert butyl ether (MTBE)	μg/L					1.0 U								
Methylene chloride Styrene	μg/L					5.0 U 1.0 U								
Tetrachloroethene	μg/L μg/L					1.0 U		 		 	 	 		
Toluene	μg/L					1.0 U		 						
trans-1,2-Dichloroethene	μg/L					1.0 U								
trans-1,3-Dichloropropene	μg/L					1.0 U								
Trichloroethene	μg/L					1.0 U								
Trichlorofluoromethane (CFC-11) Trifluorotrichloroethane (CFC-113)	μg/L					1.0 U 1.0 U								
Vinyl chloride	μg/L μg/L	 0.98 J	 			1.0 U		 		 		 		
Xylenes (total)	μg/L					2.0 U		 						
. ,	. 0													

Sample Location Sample Date Parameters	Units	MW-X169Y058S-1 11/15/2023	MW-X227Y054 11/14/2023	MW-X242Y060S 11/14/2023	MW-X261Y356D-3 11/14/2023	MW-X277Y100 11/16/2023	MW-X297Y305D-2 11/14/2023	MW-X300Y199I-1 11/14/2023	MW-X300Y199I-2 11/14/2023	MW-X315Y115 11/14/2023	MW-X315Y150 11/14/2023	MW-X315Y150 11/14/2023	ST-59 11/16/2023	Tributary 3-3 11/16/2023
General Chemistry														
Chloride	μg/L								-			-	15000	
Field Parameters														
Conductivity, field	uS/cm	1.811	1126	863	0.523	1.447	0.641	0.447	0.669	450	266	266	311	566
Dissolved oxygen (DO), field	μg/L	29000	1010	1660	1680	1690	810	560	2990	1210	3030	3030	12890	13270
Flow rate	mL/min		500	500						500	500	500		
Oxidation reduction potential (ORP), field	millivolts	-52.4	-111.8	-83.2	81.5	-115.8	-71.7	-123.0	-132.2	-1.3	-64.6	-64.6	103.2	105.8
pH, field	s.u.	7.55	7.81	7.28	7.11	6.97	7.03	7.43	7.11	7.50	7.57	7.57	7.98	7.96
Temperature, sample	Deg C	15.25	15.26	14.19	15.84	14.08	14.63	14.53	15.49	14.48	14.72	14.72	15.34	12.87
Turbidity, field	NTU	15.9	16.1	12.8	12.6	5.23	19.9	9.56	12.1	12.4	63.0	63.0		
Volume purged	gal	ND	4.82		ND		ND	ND		3.69			ND	ND

Notes:
U - Not detected at the associated reporting limit.
J - Estimated concentration.
UJ - Not detected; associated reporting limit is estimated.

Page 1 of 2

2023 LCS and LDS Analytical Results East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Sample Location Sample Date Sample Type Parameters	Units	EPA LCS 01/09/2023	EPA LCS 02/06/2023	EPA LCS 03/14/2023	EPA LCS 04/10/2023	EPA LCS 05/15/2023	EPA LCS 05/15/2023 Duplicate	EPA LCS 06/13/2023	EPA LCS 07/17/2023	EPA LCS 08/07/2023	EPA LCS 09/11/2023	EPA LCS 10/12/2023	EPA LCS 11/09/2023	EPA LCS 12/07/2023
Polychlorinated biphenyl (PCBs)														
Aroclor-1016 (PCB-1016) Aroclor-1221 (PCB-1221) Aroclor-1232 (PCB-1232) Aroclor-1242 (PCB-1242) Aroclor-1248 (PCB-1248) Aroclor-1254 (PCB-1254) Aroclor-1260 (PCB-1260) Total PCBs	ug/L ug/L ug/L ug/L ug/L ug/L ug/L	0.095 U 0.095 U 0.095 U 0.19 P 0.095 U 0.095 U 0.095 U 0.19 P	0.095 U 0.095 U 0.095 U 0.22 0.095 U 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.83 0.095 U 0.095 U 0.095 U 0.83	0.095 U 0.095 U 0.095 U 0.56 0.095 U 0.095 U 0.095 U 0.56	0.48 U 0.48 U 0.48 U 0.69 P 0.48 U 0.48 U 0.48 U 0.69 P	0.48 U 0.48 U 0.48 U 0.56 P 0.48 U 0.48 U 0.48 U 0.56 P	0.095 U 0.095 U 0.095 U 0.45 0.095 U 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.37 P 0.095 U 0.095 U 0.095 U 0.37 P	0.095 U 0.095 U 0.095 U 0.095 U 0.30 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.38 0.095 U 0.095 U 0.095 U	0.095 U 0.095 U 0.095 U 0.34 0.095 U 0.095 U 0.095 U 0.34	0.095 U 0.095 U 0.095 U 0.36 0.095 U 0.095 U 0.095 U 0.36	0.095 U 0.095 U 0.095 U 0.16 p 0.095 U 0.095 U 0.095 U 0.16 P
Volatile Organic Compounds (VOCs)	-3-2													
1,1,1-Trichloroethane 1,1,2,2-Tetrachloroethane 1,1,2-Trichloroethane 1,1-Dichloroethane 1,1-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 1,2-Dichloroethane 1,3-Dichlorobenzene 1,3-Dichlorobenzene 2-Chloroethyl vinyl ether Benzene Bromodichloromethane Bromoform Bromomethane (Methyl bromide) Carbon tetrachloride Chlorobenzene Chloroetnane Chloroetnane Chloromethane (Methyl chloride) cis-1,3-Dichloropropene Dibromochloromethane Dichlorodifluoromethane Dichlorodifluoromethane Toluene trans-1,2-Dichloroethene trans-1,3-Dichloropropene Trichlorofluoromethane Toluene trans-1,3-Dichloropropene Trichlorofluoromethane (CFC-11) Vinyl chloride	ug/L ug/L ug/L ug/L ug/L ug/L ug/L ug/L	1.0 U	1.0 UH	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U 1.0 U 1.0 U 1.0 U 1.0 U*+ 1.0 U
General Chemistry	ug/L	1.0 0	1.0 011	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0	1.0 0
Sulfate Total organic carbon (TOC) Field Parameters	ug/L ug/L	 	- -	 	 	 	-	 	=	-	<u></u>	 	 	
Conductivity, field Dissolved oxygen (DO), field Oxidation reduction potential (ORP), field pH, field Temperature, sample	mS/cm ug/L millivolts s.u. Deg F	3.69 7820 70 6.7 53.78	2.91 7820 241 6.7 57.02	2.47 5260 166 7.3 52.34	2.27 7470 331 7 66.56	2.47 10590 2.35 62.96	2.47 10590 2.35 62.96	26.1 9230 -24 6.8 64.76	2.47 6650 -60 6.7 69.44	4.39 -5 6.8 71.78	2.92 6110 -33 7 69.08	2.98 7510 13 7 62.78	2.15 5980 -39 7 61.34	3.58 7180 46 7 53.24

2023 LCS and LDS Analytical Results East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Bedford, Indiana

Sample Location Sample Date Sample Type Parameters	Units	EPA LDS 01/09/2023	EPA LDS 02/06/2023	EPA LDS 03/14/2023	EPA LDS 05/15/2023	EPA LDS 06/13/2023	EPA LDS 06/13/2023 Duplicate	EPA LDS 07/17/2023	EPA LDS 08/07/2023	EPA LDS 09/11/2023	EPA LDS 10/12/2023	EPA LDS 11/09/2023	EPA LDS 11/09/2023 Duplicate
Polychlorinated biphenyl (PCBs)													
Aroclor-1016 (PCB-1016)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U					
Aroclor-1221 (PCB-1221)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U					
Aroclor-1232 (PCB-1232)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U					
Aroclor 1242 (PCB-1242)	ug/L	0.095 U 0.095 U	0.095 U 0.095 U	0.11 p	0.13 0.095 U	0.15 0.095 U	0.16 0.095 U	0.095 U 0.095 U	0.095 U 0.095 U	0.11 0.095 U	0.095 U 0.095 U	0.095 U 0.095 U	0.095 U 0.095 U
Aroclor-1248 (PCB-1248) Aroclor-1254 (PCB-1254)	ug/L	0.095 U	0.095 U	0.095 U 0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U
Aroclor-1260 (PCB-1260)	ug/L ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U					
Total PCBs	ug/L	ND	ND	0.11 P	0.13	0.15	0.16	ND	ND	0.11	ND	ND	ND
Volatile Organic Compounds (VOCs)													
1,1,1-Trichloroethane	ug/L												
1,1,2,2-Tetrachloroethane	ug/L							<u></u>				<u></u>	
1,1,2-Trichloroethane	ug/L												
1,1-Dichloroethane	ug/L												
1,1-Dichloroethene	ug/L												
1,2-Dichlorobenzene	ug/L												
1,2-Dichloroethane	ug/L												
1,2-Dichloropropane	ug/L												
1,3-Dichlorobenzene	ug/L												
1,4-Dichlorobenzene	ug/L												
2-Chloroethyl vinyl ether	ug/L												
Benzene	ug/L												
Bromodichloromethane	ug/L												
Bromoform	ug/L												
Bromomethane (Methyl bromide)	ug/L												
Carbon tetrachloride	ug/L												
Chlorobenzene	ug/L												
Chloroethane	ug/L												
Chloroform (Trichloromethane)	ug/L												
Chloromethane (Methyl chloride)	ug/L												
cis-1,3-Dichloropropene	ug/L												
Dibromochloromethane	ug/L												
Dichlorodifluoromethane (CFC-12)	ug/L												
Ethylbenzene Mathylara a blasida	ug/L												
Methylene chloride Tetrachloroethene	ug/L												
Toluene	ug/L	 						 		 	 		
trans-1,2-Dichloroethene	ug/L ug/L	 		 	 	 	 	 	 	 	 	 	
trans-1,3-Dichloropropene	ug/L	 	-				 	 	 	 	 	 	
Trichlorofluoromethane (CFC-11)	ug/L			 	 	 	 	 	 	 	 	 	
Vinyl chloride	ug/L												
General Chemistry													
Sulfate	ug/L												
Total organic carbon (TOC)	ug/L												
Field Parameters													
Conductivity, field	mS/cm	2.55	2.42	2.73	2.57	1641	1641	2.51	2.34	3.83	2.71	2.11	2.11
Dissolved oxygen (DO), field	ug/L	8400	11170	9010	14700	13450	13450	13300		6090	6200	4080	4080
Oxidation reduction potential (ORP), field	millivolts	112	173	135	2.54	-15	-15	-2	8	-47	-18	-54	-54
pH, field	s.u.	7.5	7.5	8		7.3	7.3	6.9	6.9	6.9	6.7	7	7
Temperature, sample	Deg F	53.06	58.28	55.4	61.7	65.66	65.6	68	70.93	68.9	62.08	62.24	62.24

Notes:

U - Not detected at the associated reporting limit.

P - The %RPD between the primary and confirmation column.detector is >40%. The lower value has been reported.
H - Sample was prepped or analyzed beyond the specific holding time.
*+ - LCS and/or LCSD is outside acceptance limits, high biased.


2023 Groundwater Treatment Plant Monitoring Analytical Results East Plant Area TSCA Vault Annual Report, Calendar Year 2023 GM Bedford Casting Operations Facility Beford, Indiana


Sample Location Sample Date Sample Type Parameters	Units	HV-6021A 01/09/2023	HV-6021A 02/06/2023	HV-6021A 03/14/2023	HV-6021A 04/10/2023	HV-6021A 05/15/2023	HV-6021A 06/13/2023	HV-6021A 07/17/2023	HV-6021A 08/07/2023	HV-6021A 09/11/2023	HV-6021A 09/11/2023 Duplicate	HV-6021A 10/12/2023	HV-6021A 10/12/2023 Duplicate	HV-6021A 11/09/2023	HV-6021A 12/07/2023
Polychlorinated biphenyl (PCBs)															
Aroclor-1016 (PCB-1016)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Aroclor-1221 (PCB-1221)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Aroclor-1232 (PCB-1232)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Aroclor-1242 (PCB-1242)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Aroclor-1248 (PCB-1248)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Aroclor-1254 (PCB-1254)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Aroclor-1260 (PCB-1260)	ug/L	0.095 U	0.095 U	0.095 U	0.095 U	0.095 U									
Total PCBs	ug/L	ND	ND	ND	ND	ND									
General Chemistry															
Total suspended solids (TSS)	ug/L	-		-				4000 U	-			-			
Field Parameters															
pH, field	s.u.	7	7	7	7	7	7	7	7	7	7	7	7	7	7


Notes:


U Not detected at the associated reporting limit.

Figures











LCS Flow Meter

LDS Flow Meter

LCS flow meter readings from 2021have been excluded due false positive flow being recorded at PLC

LCS flow meter readings for the first half of 2022 have been excluded due false positive flow being recorded at PLC

The recorded volume of water removed from the LCS from Novermber 2021-June 2022 contain discrepencies due to signal fluctuations (drift) and are not included in the chart development

Figure 5.1

SUMMARY OF AVERAGE MONTHLY VOLUME OF WATER REMOVED FROM LCS AND LDS EAST PLANT AREA TSCA VAULT ANNUAL REPORT, CALENDAR YEAR 2023 **GM BEDFORD CASTING OPERATIONS FACILITY** Bedford, Indiana

Appendices

Appendix A

Cover System Inspection Forms

Date of Inspection:	11/20/2023	Weather:	Overcast
Inspector:	Scott Sholar	Temperatu re:	33

		СН	ECKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
VEGETATE	ED SOIL COVER SYS	TEM			1		
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	Ø					
	EXPPOSURE OF LINER	√					
Transect	- EROSION	√					
EV5	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	7					
	- SIGNS OF BURROWING BY ANIMALS	7					
	- ROOTING OF TREES	7					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	1					
Transect	- EROSION	7					
EV4	- LOCALIZED SETTLEMENT/SLUMP ING	7					
	- PONDING OF WATER/DRAINAGE	1					
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES	7					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	√					
Transect	- EROSION						
EV3	- LOCALIZED SETTLEMENT/SLUMP ING						
	- PONDING OF WATER/DRAINAGE	7					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	7					
Transect	- EROSION	√					
EV2	- LOCALIZED SETTLEMENT/SLUMP ING	1					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	7					
	- ROOTING OF TREES	7					

	TYPES OF	СН	ECKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
VEGETATE	D SOIL COVER SYS	TEM .					
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	7					
Transect	- EROSION	7					
EV1	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS		√		Overgrown		
	EXPPOSURE OF LINER	√					
Transect EV6	- EROSION	√					
EVO	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	1					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	√					
Transect	- EROSION	√					
EV7	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS		7		Under construction.		
	EXPPOSURE OF LINER	√					
Transect EV8	- EROSION		4				
LVO	- LOCALIZED SETTLEMENT/SLUMP ING	7					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	√					
Transect EV9	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS		V		Overgrown		
	EXPPOSURE OF LINER	7					

BEDFORD, INDIANA

		СНІ	ECKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
VEGETAT	ED SOIL COVER SYS				1		
		\checkmark					
	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	\checkmark					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	\checkmark					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	\checkmark					
Transect WV1	- EROSION	√					
WV1	- LOCALIZED SETTLEMENT/SLUMP ING	\checkmark					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	\checkmark					
						•	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	DETAILED ACTIONS REQUIRED	NOTES	DATE AND NATURE OF ACTIONS COMPLETED	EXTRA NOTES
HARD SU	RFACE COVER SYST - QUALITY OF				1		
Transect	ASPHALT COVER	√	Ш				
EA1	- PRESENCE OF CRACKING OR DISCOLORATION - QUALITY OF				Slight discoloration		
Transect	ASPHALT COVER	\checkmark					
EA2	- PRESENCE OF CRACKING OR DISCOLORATION		4		Slight discoloration		
Transect	- QUALITY OF ASPHALT COVER	7					
WA1	- PRESENCE OF CRACKING OR DISCOLORATION				Slight discoloration		
ACCESS F			_				
	-						
Phase II Trench	OBSTRUCTIONS/DEBRI S	V	Ш				
Access	- POTHOLES	\checkmark					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC	7					
	- EROSION						
Vault	OBSTRUCTIONS/DEBRI						
Access	- POTHOLES	7					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC	\checkmark					
	- EROSION	4					
GWTP Parking	- OBSTRUCTIONS/DEBRI S				Covered with stone backfill with ongoing pilot trench construction.		
	- POTHOLES	\checkmark					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC						
Pilot	- EROSION	V					
Trench		+					+

 \checkmark

Access

OBSTRUCTIONS/DEBRI

	TYPES OF PROBLEMS	CHECKED		DETAILED		DATE AND	
ITEM		NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
HARD SURFACE COVER SYSTEMS							
	- POTHOLES	7					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC						

							1
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CKED CORRECTIVE ACTION REQUIRED	DETAILED ACTIONS REQUIRED	NOTES	DATE AND NATURE OF ACTIONS COMPLETED	EVTDA NOTES
SWALE/DR	AINAGE DITCHES					COMPLETED	EXTRA NOTES
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	7					
Transect ES10	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	 ✓					
	ACCUMULATION - CULVERT/CATCH BASIN	4					
	- SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES	4					
		√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	Z					
Transect ES11	EROSION	4					
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION	4					
	- CULVERT/CATCH BASIN	√					
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES QUALITY OF	√					
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	7					
Transect ES9	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION	V					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES	√					

		СНЕ	CKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
SWALE/DR	QUALITY OF						
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS						
	- GRASS COVERAGE - NOXIOUS WEEDS						
		4	Ш				
Transect ES8	EROSION	1					
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	4					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES						
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS						
	- DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
		√					
Transect	EROSION	✓					
ES7	- OBSTRUCTIONS - OBSTRUCTIONS						
	- SEDIMENT ACCUMULATION - CULVERT/CATCH	1					
	BASIN - SIGNS OF	7					
	BURROWING BY ANIMALS - ROOTING OF TREES	7					
	QUALITY OF	7					
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS						
	- GRASS COVERAGE - NOXIOUS WEEDS						
		√					
Transect ES6	EROSION		П				
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	√	П				
	ACCUMULATION - CULVERT/CATCH BASIN	<u> </u>					
	- SIGNS OF BURROWING BY	√					
	ANIMALS - ROOTING OF TREES	7					
	QUALITY OF VEGETATIVE COVER						
	- LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE						
Transc-t	- NOXIOUS WEEDS						
Transect ES5		_	_				
	EROSION	4					

		СНЕ	CKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
SWALE/DR	- OBSTRUCTIONS			T			
	- OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH	 ✓					
	BASIN	4					
	- SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES	4					
		√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	7					
Transect ES4	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	Ø					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY						
	- ROOTING OF TREES						
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	Z					
Transect ES3	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT						
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES			Cutting of saplings	3 small trees beginning to grow.		
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
Transect ES2	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	 ✓					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES	√					

		CHE	CKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
SWALE/DR	QUALITY OF				Tall grass.		
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS						
	- GRASS COVERAGE - NOXIOUS WEEDS						
			\checkmark				
Transect	EROSION						
ES12	- OBSTRUCTIONS		Ш				
	- OBSTRUCTIONS - SEDIMENT ACCUMULATION	√					
	- CULVERT/CATCH BASIN	√					
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES	4					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS				Overgrown		
	- DEAD/DYING GRASS - GRASS COVERAGE						
	- NOXIOUS WEEDS		\checkmark				
Transect ES13	EROSION		√		Construction activities ongoing.		
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	П	√		Construction activity ongoing		
	- CULVERT/CATCH						
	- SIGNS OF BURROWING BY	<u> </u>					
	ANIMALS - ROOTING OF TREES	√					
	QUALITY OF	4					
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS						
	- GRASS COVERAGE - NOXIOUS WEEDS						
			Ш				
Transect ES1	EROSION						
LSI	- OBSTRUCTIONS - OBSTRUCTIONS						
	- SEDIMENT ACCUMULATION	1					
	- CULVERT/CATCH BASIN	7					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	4					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS				Overgrown, tall grass.		
	- DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
Transect			\checkmark				
ES14							
	EROSION	√					

	TYPES OF PROBLEMS	CHE	CKED	DETAILED		DATE AND		
ITEM		NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES	
SWALE/DR	SWALE/DRAINAGE DITCHES							
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION	4						
	- CULVERT/CATCH BASIN							
	- SIGNS OF BURROWING BY ANIMALS	4						
	- ROOTING OF TREES							

		CHE	CKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
PERIMETE	R GROUNDWATER CO	NTROL SYSTEM					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
PGCS 1	EROSION	√					
	LOCALIZED SETTLEMENT/SLUMPIN G						
	PONDING OF WATER/DRAINAGE						
	- ROOTING OF TREES	7					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
PGCS 2	EROSION	7					
	LOCALIZED SETTLEMENT/SLUMPIN G						
	PONDING OF WATER/DRAINAGE	7					
	- ROOTING OF TREES	√					

Date of Inspection:	11/20/2023	Weather:	Overcast
Inspector:	Scott Sholar	Temperatu re:	33

		CHECKED		DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
VEGETATE	ED SOIL COVER SYS	TEM			1		
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	Ø					
	EXPPOSURE OF LINER	√					
Transect	- EROSION	√					
EV5	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	7					
	- SIGNS OF BURROWING BY ANIMALS	7					
	- ROOTING OF TREES	7					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	1					
Transect	- EROSION	7					
EV4	- LOCALIZED SETTLEMENT/SLUMP ING	7					
	- PONDING OF WATER/DRAINAGE	1					
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES	7					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	√					
Transect	- EROSION						
EV3	- LOCALIZED SETTLEMENT/SLUMP ING						
	- PONDING OF WATER/DRAINAGE	7					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	7					
Transect EV2	- EROSION	√					
EVZ	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	7					
	- SIGNS OF BURROWING BY ANIMALS	7					
	- ROOTING OF TREES	7					

	TYPES OF	CHECKED		DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
VEGETATE	D SOIL COVER SYS	STEM					
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	7					
Transect	- EROSION						
EV1	- LOCALIZED SETTLEMENT/SLUMP ING	7					
	- PONDING OF WATER/DRAINAGE	7					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS		√		Overgrown		
	EXPPOSURE OF LINER	√					
Transect EV6	- EROSION	√					
EVO	- LOCALIZED SETTLEMENT/SLUMP ING						
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES	1					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	√					
Transect EV7	- EROSION	√					
EV/	- LOCALIZED SETTLEMENT/SLUMP ING						
	- PONDING OF WATER/DRAINAGE						
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES	1					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS		7		Under construction.		
	EXPPOSURE OF LINER	√					
Transect EV8	- EROSION		4				
LVO	- LOCALIZED SETTLEMENT/SLUMP ING	4					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES	4					
Transect EV9	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS		√		Overgrown		
	EXPPOSURE OF LINER	4					

BEDFORD, INDIANA

		СНІ	ECKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
VEGETAT	ED SOIL COVER SYS				1		
		\checkmark					
	- LOCALIZED SETTLEMENT/SLUMP ING	√					
	- PONDING OF WATER/DRAINAGE	\checkmark					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	\checkmark					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
	EXPPOSURE OF LINER	\checkmark					
Transect WV1	- EROSION	√					
WV1	- LOCALIZED SETTLEMENT/SLUMP ING	\checkmark					
	- PONDING OF WATER/DRAINAGE	√					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES	\checkmark					
						•	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	DETAILED ACTIONS REQUIRED	NOTES	DATE AND NATURE OF ACTIONS COMPLETED	EXTRA NOTES
HARD SU	RFACE COVER SYST - QUALITY OF				1		
Transect	ASPHALT COVER	√	Ш				
EA1	- PRESENCE OF CRACKING OR DISCOLORATION - QUALITY OF		4		Slight discoloration		
Transect	ASPHALT COVER	\checkmark					
EA2	- PRESENCE OF CRACKING OR DISCOLORATION		4		Slight discoloration		
Transect	- QUALITY OF ASPHALT COVER	7					
WA1	- PRESENCE OF CRACKING OR DISCOLORATION				Slight discoloration		
ACCESS F			_				
	-						
Phase II Trench	OBSTRUCTIONS/DEBRI S	V	Ш				
Access	- POTHOLES	\checkmark					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC	7					
	- EROSION						
Vault	OBSTRUCTIONS/DEBRI						
Access	- POTHOLES	7					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC	\checkmark					
	- EROSION	4					
GWTP Parking	- OBSTRUCTIONS/DEBRI S				Covered with stone backfill with ongoing pilot trench construction.		
	- POTHOLES	\checkmark					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC						
Pilot	- EROSION	V					
Trench		+					+

 \checkmark

Access

OBSTRUCTIONS/DEBRI

		CH	ECKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
HARD SUI	RFACE COVER SYSTE	MS					
	- POTHOLES	7					
	- DAMAGE CAUSED BY VEHICULAR TRAFFIC						

ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CKED CORRECTIVE ACTION REQUIRED	DETAILED ACTIONS REQUIRED	NOTES	DATE AND NATURE OF ACTIONS COMPLETED	EVTDA NOTES
SWALE/DR	AINAGE DITCHES					COMPLETED	EXTRA NOTES
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	7					
Transect ES10	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	 ✓					
	ACCUMULATION - CULVERT/CATCH BASIN	4					
	- SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES	4					
		√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	Z					
Transect ES11	EROSION	4					
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION	4					
	- CULVERT/CATCH BASIN	7					
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES QUALITY OF	√					
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	7					
Transect ES9	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION						
	- CULVERT/CATCH BASIN	4					
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES	√					

Transect ES8 CORRECTIVE ACTIONS REQUIRED NOTES NATURE OF ACTIONS REQUIRED	EXTRA NOTES
Transect ES8 EROSION OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH BASIN SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES QUALITY OF	
Transect ES8 EROSION OBSTRUCTIONS OBSTRUCTIONS SEDIMENT ACCUMULATION - SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES OLATIVE ACCUMULATY OF	
Transect ES8 EROSION	
Transect ES8 EROSION OBSTRUCTIONS OBSTRUCTIONS SEDIMENT ACCUMULATION CULVERT/CATCH BASIN SIGNS OF BURROWING BY ANIMALS ROOTING OF TREES QUALITY OF	
ES8 - OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH BASIN - SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES - QUALITY OF	
ES8 - OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH BASIN - SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES - QUALITY OF	
- OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH BASIN - SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES QUALITY OF	
- CULVERT/CATCH BASIN - SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES QUALITY OF	
BURROWING BY ANIMALS - ROOTING OF TREES QUALITY OF	
- ROOTING OF TREES QUALITY OF	
QUALITY OF VEGETATIVE COVER	
- LENGTH OF GRASS	
- DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	
Transect ES7 FROSION	
- OBSTRUCTIONS	
- OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH	
- COLVENIZATOR	
BURROWING BY ANIMALS - ROOTING OF TREES	
QUALITY OF	
VOGETIATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS	
- GRASS COVERAGE - NOXIOUS WEEDS	
Transect ES6 EROSION	
- OBSTRUCTIONS - OBSTRUCTIONS	
ACCUMULATION CITY TO THE TOTAL TO THE T	
- COLVENT/CATCH BASIN - SIGNS OF DUPPONING BY	
BURROWING BY ANIMALS - ROOTING OF TREES	
QUALITY OF VEGETATIVE COVER	
VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE	
- NOXIOUS WEEDS	
Transect ES5	
EROSION	

		СНЕ	CKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
SWALE/DR	- OBSTRUCTIONS						
	- OBSTRUCTIONS - SEDIMENT ACCUMULATION - CULVERT/CATCH	 ✓					
	BASIN	4	Ш				
	- SIGNS OF BURROWING BY ANIMALS - ROOTING OF TREES	4					
		√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	7					
Transect ES4	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	Ø					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY						
	- ROOTING OF TREES						
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD//DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	Z					
Transect ES3	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT						
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS						
	- ROOTING OF TREES			Cutting of saplings	3 small trees beginning to grow.		
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
Transect ES2	EROSION						
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT	 ✓					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS	 ✓					
	- ROOTING OF TREES	√					

		CHECKED				DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	DETAILED ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
SWALE/DR	QUALITY OF				Tall grass.		
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS						
	- GRASS COVERAGE - NOXIOUS WEEDS						
			\checkmark				
Transect	EROSION						
ES12	- OBSTRUCTIONS		Ш				
	- OBSTRUCTIONS - SEDIMENT ACCUMULATION	√					
	- CULVERT/CATCH BASIN	7					
	- SIGNS OF BURROWING BY ANIMALS	√					
	- ROOTING OF TREES						
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS				Overgrown		
	- DEAD/DYING GRASS - GRASS COVERAGE						
	- NOXIOUS WEEDS		\checkmark				
Transect ES13	EROSION		√		Construction activities ongoing.		
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT		√		Construction activity ongoing		
	ACCUMULATION - CULVERT/CATCH BASIN	✓					
	- SIGNS OF BURROWING BY	√					
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER						
	- LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE						
	- NOXIOUS WEEDS						
Transect ES1	EROSION	7					
	- OBSTRUCTIONS - OBSTRUCTIONS	<u> </u>					
	- SEDIMENT ACCUMULATION - CULVERT/CATCH						
	- SIGNS OF	7					
	BURROWING BY ANIMALS - ROOTING OF TREES	7					
	QUALITY OF	7			Overgrown, tall		
	VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS				grass.		
	- GRASS COVERAGE - NOXIOUS WEEDS						
Transect ES14			\checkmark				
2314							
	EROSION						
		I	Ш				

		CHE	CKED	DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
SWALE/DR							
	- OBSTRUCTIONS - OBSTRUCTIONS - SEDIMENT ACCUMULATION	4					
	- CULVERT/CATCH BASIN						
	- SIGNS OF BURROWING BY ANIMALS	4					
	- ROOTING OF TREES						

		CHECKED		DETAILED		DATE AND	
ITEM	TYPES OF PROBLEMS	NO PROBLEMS	CORRECTIVE ACTION REQUIRED	ACTIONS REQUIRED	NOTES	NATURE OF ACTIONS COMPLETED	EXTRA NOTES
PERIMETE	R GROUNDWATER CO	NTROL SYSTEM					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS						
PGCS 1	EROSION	√					
	LOCALIZED SETTLEMENT/SLUMPIN G						
	PONDING OF WATER/DRAINAGE						
	- ROOTING OF TREES	√					
	QUALITY OF VEGETATIVE COVER - LENGTH OF GRASS - DEAD/DYING GRASS - GRASS COVERAGE - NOXIOUS WEEDS	V					
PGCS 2	EROSION	√					
	LOCALIZED SETTLEMENT/SLUMPIN G						
	PONDING OF WATER/DRAINAGE						
	- ROOTING OF TREES	√					



→ The Power of Commitment